

THM PA 60/40 WS**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The THM labels offer brilliant printing quality thanks to the thermal transfer technology. Different materials and the user-friendly printing system under Windows optimise every marking effort.

- High-quality polyester labels in various colours or inexpensive paper labels are available
- Labels are automatically positioned in the printer for perfectly centred prints on each label.

General ordering data

Version	THM, Device markers, {Reference (AttributeDefinition) not found: pAttr74196859207437}
Order No.	1244760000
Type	THM PA 60/40 WS
GTIN (EAN)	4050118032567
Qty.	1 pc(s).
compatible printer	2599430000 2599440000

Creation date March 23, 2021 12:13:54 PM CET

THM PA 60/40 WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	0.08 mm	Depth (inches)	0.003 inch
Height	40 mm	Height (inches)	1.575 inch
Net weight	773 g	Width	60 mm
Width (inches)	2.362 inch		

Temperatures

Operating temperature range	-40...70 °C
-----------------------------	-------------

General data

Adhesive	Permanent acrylic copolymer	Material	Paper
Number of markers per combination	1 Label reel = Device markers	Number per roll	2,000
Number per sheet	2,000	Operating temperature range	-40...70 °C
Operating temperature range, max.	70 °C	Operating temperature range, min.	-40 °C
Printing method	Thermal transfer	UL 94 flammability rating	HB
Width	60 mm		

Classifications

ETIM 6.0	EC001288	ETIM 7.0	EC001288
ECLASS 9.0	27-40-06-29	ECLASS 9.1	27-40-06-29
ECLASS 10.0	27-40-06-29	ECLASS 11.0	27-28-11-04

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD

THM PA 60/40 WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

