

TPSDHA KTB 100X25 S2 2R

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Similar to illustration







Integrate, expand and customise: The ideal expansion for every application

The consistent structure of accessories for the new Klippon[®] TB enclosure range means that you can easily adapt the enclosure to the specific requirements of each application.

Nameplate holders

There are a variety of designed label holders available for prominent display as required and for additional nameplates as needed.

General ordering data

Version	Klippon TB (Terminal Box), Ratings plate holder, Riveted, Height: 25 mm, Width: 141 mm, Depth: 16.5 mm, Material: Stainless steel 1.4301, Mirror polished, silver
Order No.	<u>1257640000</u>
Туре	TPSDHA KTB 100X25 S2 2R
GTIN (EAN)	4050118070354
Qty.	1 pc(s).



TPSDHA KTB 100X25 S2 2R

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

-			
Dım	ensions	and	weights

Depth	16.5 mm	Depth (inches)	0.65 inch
Height	25 mm	Height (inches)	0.984 inch
Net weight	34 g	Width	141 mm
Width (inches)	5.551 inch		

General information

Stainless steel 1.4301	Material thickness	1 mm
Mounting is possible in any position on the lid, including inside the sealed area of the housing. The lid seal must, however, not be damaged. To guarantee a 100% seal, the assembly must be done using the fixing material, 1252190000 TPSD FIXING SET KTB. The attachment of the rating plate is done individually onto the rating plate holder. We recommend the use of fixing material 1285200000 SD FIXING SET for mounting.	Surface finish	Mirror polished
	Mounting is possible in any position on the lid, including inside the sealed area of the housing. The lid seal must, however, not be damaged. To guarantee a 100% seal, the assembly must be done using the fixing material, 1252190000 TPSD FIXING SET KTB. The attachment of the rating plate is done individually onto the rating plate holder. We recommend the use of fixing material 1285200000 SD FIXING	Mounting is possible in any position on the lid, including inside the sealed area of the housing. The lid seal must, however, not be damaged. To guarantee a 100% seal, the assembly must be done using the fixing material, 1252190000 TPSD FIXING SET KTB. The attachment of the rating plate is done individually onto the rating plate holder. We recommend the use of fixing material 1285200000 SD FIXING

General information on accessories

O. C. C. L.	
Surface finish Mirror polished	

Classifications

ETIM 6.0	EC002626	ETIM 7.0	EC002626
ECLASS 9.0	27-18-28-16	ECLASS 9.1	27-18-92-90
ECLASS 10.0	27-18-28-16	ECLASS 11.0	27-18-28-16

Approvals

ROHS	Conform

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD