

## CA 100 C

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



- For automatic stripping and crimping
- Time-saving and efficient processing
- Easily adjustable to the respective cross-section range
- Stripping and crimping in one work step
- The processing of sleeves or contacts from other manufacturers can cause machine failures and defects!

### General ordering data

|            |                                |
|------------|--------------------------------|
| Version    | Automatic stripper and crimper |
| Order No.  | <a href="#">1266370000</a>     |
| Type       | CA 100 C                       |
| GTIN (EAN) | 4050118056303                  |
| Qty.       | 1 pc(s).                       |

## CA 100 C

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |          |                 |             |
|------------|----------|-----------------|-------------|
| Depth      | 280 mm   | Depth (inches)  | 11.024 inch |
| Height     | 390 mm   | Height (inches) | 15.354 inch |
| Net weight | 28,000 g | Weight          | 23 kg       |
| Width      | 410 mm   | Width (inches)  | 16.142 inch |

## Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

## PW65 maintenance - automatic stripping/crimping

|                                       |                      |                                       |                                                   |
|---------------------------------------|----------------------|---------------------------------------|---------------------------------------------------|
| Compressed-air connection             | 5 bar                | Consumables                           | loose cable lugs, With and without plastic collar |
| Crimping length                       | 6/8 mm               | Drive                                 | Electropneumatic                                  |
| Electrical connection                 | 100-240 V / 50/65 Hz | Length of wire-end ferrule            | 12/14 mm                                          |
| Pulse time                            | approx. 1.5 s        | Stripping range                       | 0.14 - 0.34 mm <sup>2</sup> (~ AWG 26 - 22)       |
| Wire end ferrules cross-section, max. | 0.34 mm <sup>2</sup> | Wire end ferrules cross-section, min. | 0.14 mm <sup>2</sup>                              |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002778    | ETIM 7.0    | EC002778    |
| ECLASS 9.0  | 17-13-01-01 | ECLASS 9.1  | 17-13-01-01 |
| ECLASS 10.0 | 17-13-01-01 | ECLASS 11.0 | 17-13-01-01 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                    |                          |
|--------------------|--------------------------|
| User Documentation | <a href="#">CA 100 C</a> |
|--------------------|--------------------------|

## CA 100 C

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

