

S5-135 TO S7 CONV_1OUT**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The front adapters for migration are connected to the old PLC and, by means of a new pre-assembled cable, to the new one. Some adapters have 2 connectors for redundancy.

General ordering data

Order No.	1273320000
Type	S5-135 TO S7 CONV_1OUT
GTIN (EAN)	4050118063066
Qty.	1 pc(s).
Delivery status	Discontinued
Available until	2019-10-17

S5-135 TO S7 CONV_1OUT

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	25 mm	Height (inches)	0.984 inch
Length	315 mm	Length (inches)	12.402 inch
Net weight	50 g	Width	20 mm
Width (inches)	0.787 inch		

Temperatures

Storage temperature	-40...60 °C	Operating temperature	-25...50 °C
---------------------	-------------	-----------------------	-------------

Connection data

Connection (field side)	3 x SL 5.08/14/180	Connection to PLC	6ES5497-4UA12
-------------------------	--------------------	-------------------	---------------

Ratings data

Operating voltage	24 V AC, 24 V DC
-------------------	------------------

Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	≤ 50 V DC
Surge voltage category	III	Pollution severity level	2
Insulation test voltage	0.35 kVAC		

Classifications

ETIM 6.0	EC002584	ETIM 7.0	EC002584
ECLASS 9.0	27-33-02-92	ECLASS 9.1	27-24-22-92
ECLASS 10.0	27-33-02-92	ECLASS 11.0	27-33-02-92

Downloads

Engineering Data	EPLAN
------------------	-----------------------