

**ETA 1170 21 5A****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Similar to illustration

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |                                   |
|------------|-----------------------------------|
| Version    | Accessories, Circuit breaker, 5 A |
| Order No.  | <a href="#">1278750000</a>        |
| Type       | ETA 1170 21 5A                    |
| GTIN (EAN) | 4050118091274                     |
| Qty.       | 5 pc(s).                          |

## ETA 1170 21 5A

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 51.6 mm    | Depth (inches)  | 2.031 inch |
| Height         | 22 mm      | Height (inches) | 0.866 inch |
| Net weight     | 9.6 g      | Width           | 9.8 mm     |
| Width (inches) | 0.386 inch |                 |            |

## Temperatures

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 120 °C |
|----------------------------------|--------|----------------------------------|--------|

## Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

## Material data

|        |       |
|--------|-------|
| Colour | black |
|--------|-------|

## System specifications

|         |                |
|---------|----------------|
| Version | Fuse cartridge |
|---------|----------------|

## Additional technical data

|                     |                 |                  |         |
|---------------------|-----------------|------------------|---------|
| Installation advice | Direct mounting | Type of mounting | Plugged |
|---------------------|-----------------|------------------|---------|

## Fuse cartridges

|         |                |         |     |
|---------|----------------|---------|-----|
| Colour  | black          | Current | 5 A |
| Version | Fuse cartridge |         |     |

## General

|                     |                 |
|---------------------|-----------------|
| Installation advice | Direct mounting |
|---------------------|-----------------|

## Rating data

|               |         |               |     |
|---------------|---------|---------------|-----|
| Rated voltage | 28 V DC | Rated current | 5 A |
|---------------|---------|---------------|-----|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000035    | ETIM 7.0    | EC000035    |
| ECLASS 9.0  | 27-14-20-01 | ECLASS 9.1  | 27-14-20-01 |
| ECLASS 10.0 | 27-14-20-01 | ECLASS 11.0 | 27-14-20-01 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Engineering Data   | <a href="#">EPLAN, WSCAD</a>                    |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |