

CBDM 200/4.5 NA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Fastening of cables or bundles with ties into electrical switchgears and cabinets.

General ordering data

Version	Cable ties, {Reference (AttributeDefinition) not found: pAttr74196859207437}: {Reference (AttributeDefinition) not found: pAttr74196859207437}, Plastic, 220 N
Order No.	1279300000
Type	CBDM 200/4.5 NA
GTIN (EAN)	4008190185930
Qty.	100 pc(s).

Creation date March 23, 2021 1:44:46 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

CBDM 200/4.5 NA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	2 mm	Depth (inches)	0.079 inch
Height	203 mm	Height (inches)	7.992 inch
Net weight	1.54 g	Width	4.8 mm
Width (inches)	0.189 inch		

Temperatures

Operating temperature range	-40...100 °C
-----------------------------	--------------

Installation materials

Cable diameter, max.	50 mm	Diameter of fastening hole	6.3 mm
For re-opening	No	Material	Plastic
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Tensile strength	220 N	UL 94 flammability rating	V-2
UV-resistant	No	Version	for cable harnesses

Classifications

ETIM 6.0	EC000046	ETIM 7.0	EC000046
ECLASS 9.0	27-14-07-02	ECLASS 9.1	27-14-07-02
ECLASS 10.0	27-14-07-02	ECLASS 11.0	27-14-07-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN, WSCAD
------------------	------------------------------