

FUSE 1KV DC 2A 10/38**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Version	Accessories, Fuse
Order No.	1285490000
Type	FUSE 1KV DC 2A 10/38
GTIN (EAN)	4050118075953
Qty.	100 pc(s).

FUSE 1KV DC 2A 10/38**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	10 mm	Depth (inches)	0.394 inch
Diameter	10 mm	Height	38 mm
Height (inches)	1.496 inch	Net weight	10 g
Width	10 mm	Width (inches)	0.394 inch

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Material data

Colour	white
--------	-------

System specifications

Version	Fuse cartridge
---------	----------------

Additional technical data

Installation advice	Direct mounting	Type of mounting	Plugged
---------------------	-----------------	------------------	---------

Dimensions

Diameter	10 mm
----------	-------

Fuse cartridges

Cartridge fuse	10 x 38 mm	Characteristics	slo-blo
Colour	white	Current	2 A
Melting integral	3 A ^{2s}	Power output (@ 1.5 In)	1.2 W
Rated breaking capacity	30 kA	Version	Fuse cartridge

General

Installation advice	Direct mounting
---------------------	-----------------

Rating data

Rated voltage	1,000
---------------	-------

Classifications

ETIM 6.0	EC002936	ETIM 7.0	EC002936
ECLASS 9.0	27-14-20-90	ECLASS 9.1	27-14-20-90
ECLASS 10.0	27-14-20-90	ECLASS 11.0	27-14-20-90

Approvals

ROHS	Conform
------	---------

Downloads

User Documentation	StorageConditionsTerminalBlocks
--------------------	---