

**SAIL-7/8BG-3-1.5U****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Sensor/actuator cables are used for wiring sensors and actuators and for transmitting data or power in various applications. The moulded cable offers connected and tested connection of the plug-in connector to the cable ex-works. The cables may be exposed to a wide range of conditions, such as humidity, dust, heat, cold, shock or vibration.

The 7/8" cables tend to be used for power supply applications.

Is there something you have not managed to find or you feel needs explanation? Talk to us!

**General ordering data**

|            |                                                                                                                                                                               |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | Sensor/actuator line, One end without connector, 7/8", Number of poles : 3 (2 + PE), 1.5 m, Female socket, straight, Shielded: No, LED: No, Sheath material: PUR, Halogen: No |
| Order No.  | <a href="#">1292100150</a>                                                                                                                                                    |
| Type       | SAIL-7/8BG-3-1.5U                                                                                                                                                             |
| GTIN (EAN) | 4050118089417                                                                                                                                                                 |
| Qty.       | 1 pc(s).                                                                                                                                                                      |

Creation date March 23, 2021 2:45:31 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**SAIL-7/8BG-3-1.5U****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |       |
|------------|-------|
| Net weight | 150 g |
|------------|-------|

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Technical specifications for cable**

|                                                |                           |        |
|------------------------------------------------|---------------------------|--------|
| Bending radius, min., moving                   | 7.5 x cable diameter      |        |
| Cable length                                   | 1.5 m                     |        |
| Colour coding                                  | blue, brown, Green/yellow |        |
| Configurable cable length                      | No                        |        |
| Core cross-section                             | 1.5 mm <sup>2</sup>       |        |
| Halogen                                        | No                        |        |
| Housing main material                          | PUR                       |        |
| Insulation                                     | TPM                       |        |
| Number of poles                                | 3                         |        |
| Number of poles                                | 3 (2 + PE)                |        |
| Outer cladding in accordance with UL AWM style | 20234 (80 °C / 1000 V)    |        |
| Outer diameter                                 | 7.4 mm                    |        |
| Outside diameter                               | Diameter                  | 7.4 mm |
|                                                | Signs                     | ±      |
|                                                | Tolerance                 | 0.2 mm |
| Outside diameter                               | 7.4 mm ± 0.2 mm           |        |
| PE function                                    | Yes                       |        |
| Resistant to welding beads                     | No                        |        |
| Sheath material                                | PUR                       |        |
| Sheathing colour                               | black                     |        |
| Shielded                                       | No                        |        |
| Suitable for cable carriers                    | No                        |        |
| Temperature range, moving                      | -20...80 °C               |        |
| Temperature range, moving, max.                | 80 °C                     |        |
| Temperature range, moving, min.                | -20 °C                    |        |
| Temperature range, stationary                  | -50...80 °C               |        |
| Temperature range, stationary, max.            | 80 °C                     |        |
| Temperature range, stationary, min.            | -50 °C                    |        |
| Torsion resistance                             | 0 °/m                     |        |

**General technical data**

|                        |                       |                              |                         |
|------------------------|-----------------------|------------------------------|-------------------------|
| Coding                 | none                  | Connection thread            | 7/8"                    |
| Contact surface        | Au (Gold)             | Housing main material        | PUR                     |
| Insulation strength    | 10 <sup>8</sup> Ω     | LED                          | No                      |
| Plugging cycles        | ≥ 100                 | Pollution severity           | 3                       |
| Protection degree      | IP68, when screwed in | Rated current                | 12 A                    |
| Rated voltage          | 300 V                 | Temperature range of housing | -25...+80 °C            |
| Threaded ring material | Diecast zinc          | Version                      | Female socket, straight |
| jumpered               | No                    |                              |                         |

**SAIL-7/8BG-3-1.5U****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001855    | ETIM 7.0    | EC001855    |
| ECLASS 9.0  | 27-06-03-11 | ECLASS 9.1  | 27-06-03-11 |
| ECLASS 10.0 | 27-06-03-11 | ECLASS 11.0 | 27-06-03-11 |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E307231 |

**Downloads**

|                  |                              |
|------------------|------------------------------|
| Engineering Data | <a href="#">EPLAN, WSCAD</a> |
|------------------|------------------------------|


## SAIL-7/8BG-3-1.5U

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)


## Drawings

### Dimensioned drawing




Straight socket

### Pole scheme



Socket

### Wiring diagram



### The ideal tool: Screwty<sup>®</sup> with torque function



Light, securely screwed-in round plug-in connectors. Screwty set DM / VPE: 1 / Order No.: 1920000000 Adapters: M12, M12 F, M8, M8 F