

SAIL-M12GM8SG-4S5.5UIE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The most reliable way of achieving connections between two I/O slaves or between the control and one I/O subscriber is by way of pre-assembled cables. The line of cables covers PROFIBUS, CANopen, DeviceNet™, EtherCAT and Ethernet.

General ordering data

Version	Bus line, Connecting line, M12 / M8, Number of poles: 4, 5.5 m, Shielded: Yes, LED: No, Sheath material: PUR, Halogen: No
Order No.	1296790550
Type	SAIL-M12GM8SG-4S5.5UIE
GTIN (EAN)	4050118623833
Qty.	1 pc(s).

SAIL-M12GM8SG-4S5.5UIE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	191 g
------------	-------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical specifications for cable

Acceleration	5 m/s ²	Bending cycles	5 Mio
Bending radius, min., moving	7.5 x cable diameter	Bending radius, min., stationary	4 x cable diameter
Cable length	5.5 m	Colour coding	blue, orange, white / blue, white / orange
Configurable cable length	No	Core cross-section	0.15 mm ²
Halogen	No	Hybrid cable	No
Insulation	PP	Irradiation crosslinked	No
Number of poles	4	Outer cladding in accordance with UL AWM style	20963 (80 °C / 30 V)
Outside diameter	4.8 mm ± 0.3 mm	Resistant to welding beads	No
Sheath material	PUR	Sheathing colour	green
Shielded	Yes	Speed	180 m/min
Suitable for cable carriers	Yes	Temperature range, stationary	-40...80 °C

General technical data

Connection thread	M12 / M8	Contact surface	Gold-plated
Housing main material	PUR	Insulation strength	10 ⁸ Ω
LED	No	Plugging cycles	≥ 100
Pollution severity	3	Protection degree	IP67
Rated current	4 A	Temperature range of housing	-25...+80 °C
Threaded ring material	Brass, nickel-plated	jumpered	No

Electrical properties

Insulation strength	10 ⁸ Ω
---------------------	-------------------

Cable structure

Colour coding	blue, orange, white / blue, white / orange	Insulation	PP
Sheathing colour	green		

Electrical properties of cable

Insulation strength	10 ⁸ Ω	Rated current	4 A
Speed	180 m/min		

Mechanical and material properties of cable

Acceleration	5 m/s ²	Bending cycles	5 Mio
Halogen	No	Speed	180 m/min

SAIL-M12GM8SG-4S5.5UIE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Plug, right**

Contact surface

Gold-plated

Housing main material

PUR

Plugging cycles

≥ 100

Classifications

ETIM 6.0

EC002599

ETIM 7.0

EC002599

ECLASS 9.0

27-06-03-08

ECLASS 9.1

27-06-03-08

ECLASS 10.0

27-06-03-08

ECLASS 11.0

27-06-03-08

Approvals

ROHS

Conform

Downloads

Brochure/Catalogue

[Catalogues in PDF-format](#)

SAIL-M12GM8SG-4S5.5UIE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com


Drawings

Dimensioned drawing




Male, straight


Pole scheme



Wiring diagram




Dimensioned drawing



Male, straight

Pole scheme



The ideal tool: Screwty® with torque function



Light, securely screwed-in round plug-in connectors. Screwty set DM / VPE: 1 / Order No.: 1920000000 Adapters: M12, M12 F, M8, M8 F