

VSSC4 GDT 240VUC 2X10KA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

Überspannungsschutz mit Einzelkomponenten

Mit Gasableiter in Klemmenbauform

In der Klemmenbauform setzt man Gasableiter /
Funkenstrecken (GDT) ein. Sie sind für eine maximale
Gleichspannung zugelassen, die auf dem Bauelement
aufgedruckt ist. Jede Spannung, die größer als die
angegebene ist, wird sicher in ca. 10-100µs abgeleitet.
Gasableiter finden für größere Leistungen Verwendung.

General ordering data

Version	Surge protection for instrumentation and control, 240 V, 339 V, 20 A, IEC 61643-21
Order No.	1307880000
Type	VSSC4 GDT 240VUC 2X10KA
GTIN (EAN)	4050118146431
Qty.	5 pc(s).

Creation date March 23, 2021 3:11:40 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

VSSC4 GDT 240VUC 2X10KA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	58.5 mm	Depth (inches)	2.303 inch
Height	76 mm	Height (inches)	2.992 inch
Net weight	32.5 g	Width	6.2 mm
Width (inches)	0.244 inch		

Temperatures

Storage temperature	-40 °C...80 °C	Operating temperature	-40 °C...70 °C
Humidity	5...96 %		

Probability of failure

SIL PAPER	SIL Paper	SIL in compliance with IEC 61508	3
MTTF	11,416 Jahre	SFF	100 %
λges	10	PFH in 1*10 ⁻⁹ per hour	0

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

CSA protection data

Gas group C	IIB	Gas group D	IIA
Gas groups A, B	IIC	Input voltage, max. U _i	407 V
Internal capacity, max. C _i	0 nF	Internal inductance, max. L _i	0 μH

General data

Colour	black	Design	Terminal
Isolating function	No	Optical function display	No
Protection degree	IP20	Rail	TS 35
Segment	Measurement - Monitoring - Setting	UL 94 flammability rating	V-0
Version	Surge protection for measurement and control		

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

Rated data IEC / EN

Capacitance	4.65 pF	Discharge current I _{max} (8/20μs) wire-PE	2 x 10 kA
Discharge current I _n (8/20μs) wire-PE	5 kA	Lightning test current I _{imp} (10/350 μs)	2.5 kA
Lightning test current, I _{imp} (10/350 μs)		Max. continuous voltage, U _c (AC)	288 V
Wire-PE	2.5 kA	Number of poles	1
Max. continuous voltage, U _c (DC)	407 V	Protection level U _p (typ.)	< 1300 V
Overload - failure mode	Modus 2	Rated voltage (AC)	240 V
Rated current I _N	20 A	Requirements category acc. to IEC 61643-21	C2, C3, D1
Rated voltage (DC)	339 V	Surge current-carrying capacity C2	5 kA 8/20 μs
Standards	IEC 61643-21	Surge current-carrying capacity D1	2.5 kA 10/350 μs
Surge current-carrying capacity C3	100 A 10/1000 μs	Volume resistance	<0.1 Ω
Voltage type	AC/DC		

Creation date March 23, 2021 3:11:41 PM CET

VSSC4 GDT 240VUC 2X10KA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Further details of approvals**

GOST certificate

GOST-Zertifikat

Connection data

Type of connection	Screw connection	Tightening torque, min.	0.5 Nm
Tightening torque, max.	0.8 Nm	Clamping range, min.	0.5 mm ²
Clamping range, max.	4 mm ²	Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²	Conductor cross-section, flexible, AEH (DIN 46228-1), min.	0.5 mm ²
Conductor cross-section, flexible, AEH (DIN 46228-1), max.	4 mm ²	Connection cross-section, stranded, min.	0.5 mm ²
Connection cross-section, stranded, max.	4 mm ²		

Ratings IECEx/ATEX/cUL

cUL certificate

cUL Certificate

Classifications

ETIM 6.0	EC000943	ETIM 7.0	EC000943
ECLASS 9.0	27-13-08-07	ECLASS 9.1	27-13-08-07
ECLASS 10.0	27-13-08-07	ECLASS 11.0	27-13-08-07

Tender specification sheets

Long specification

Feed-through terminal, 12.4mm wide with gas-filled surge voltage arrester between the signal line connection and the mounting rail potential, TS 35 contact base. A signal with max. 32A can be protected here. When the terminal is fitted, a simultaneous electrically conducting contact is made between the mounting rail (earth) and the reference potential (ground) of the protection circuit in the terminal. Optical identification of the terminal based on the type of protected switching and the voltage level. The terminal can be labelled or marked.

Short specification

Feed-through terminal with gas-filled surge voltage arrester between the signal line connection and the mounting rail potential, TS 35 contact base. Version: 24V AC

Approvals

Approvals



ROHS

Conform

Creation date March 23, 2021 3:11:41 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

VSSC4 GDT 240VUC 2X10KA

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Downloads

Approval/Certificate/Document of
Conformity

[SIL Paper](#)
[Certificate of Compliance](#)
[CE PAPER](#)
[Declaration of Conformity](#)

Engineering Data

[STEP](#)

Engineering Data

[EPLAN, WSCAD](#)

User Documentation

[Instruction sheet VSSC](#)

VSSC4 GDT 240VUC 2X10KA

Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings



Similar to illustration

Circuit diagram

