

**STB 36.8/IH/WS WTL6/1****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Version    | Accessories, Socket        |
| Order No.  | <a href="#">1312560000</a> |
| Type       | STB 36.8/IH/WS WTL6/1      |
| GTIN (EAN) | 4050118181203              |
| Qty.       | 50 pc(s).                  |

## STB 36.8/IH/WS WTL6/1

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                 |            |                |            |
|-----------------|------------|----------------|------------|
| Depth           | 39.8 mm    | Depth (inches) | 1.567 inch |
| Diameter        | 6 mm       | Height         | 36.8 mm    |
| Height (inches) | 1.449 inch | Net weight     | 5.04 g     |
| Width           | 6 mm       | Width (inches) | 0.236 inch |

## Temperatures

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 100 °C |
|----------------------------------|--------|----------------------------------|--------|

## Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

## Material data

|                           |              |        |       |
|---------------------------|--------------|--------|-------|
| Material                  | Polyamide 66 | Colour | white |
| UL 94 flammability rating | V-2          |        |       |

## System specifications

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

## Additional technical data

|                     |                 |                  |                 |
|---------------------|-----------------|------------------|-----------------|
| Installation advice | Direct mounting | Type of mounting | when screwed in |
|---------------------|-----------------|------------------|-----------------|

## Dimensions

|          |      |               |         |
|----------|------|---------------|---------|
| Diameter | 6 mm | Plug-in depth | 11.1 mm |
|----------|------|---------------|---------|

## General

|                     |                 |                                   |        |
|---------------------|-----------------|-----------------------------------|--------|
| Installation advice | Direct mounting | Operating temperature range, max. | 100 °C |
|---------------------|-----------------|-----------------------------------|--------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002848    | ETIM 7.0    | EC002848    |
| ECLASS 9.0  | 27-14-11-92 | ECLASS 9.1  | 27-14-11-92 |
| ECLASS 10.0 | 27-14-11-92 | ECLASS 11.0 | 27-14-11-92 |

## Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### STB 36.8/IH/WS WTL6/1

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

Approval/Certificate/Document of  
Conformity

[EAC certificate](#)

Engineering Data

[STEP](#)

Engineering Data

[EPLAN](#)

User Documentation

[StorageConditionsTerminalBlocks](#)