

SAIL-VSA-DS-M12G-10U

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





Weidmüller can supply valve plugs as connecting lines with M12 plugs and one end without connector. The status of the valve plug is shown by an LED. Every valve plug is fitted with a protective circuit. The Weidmüller range includes valve plugs of type A, B and C to DIN and industry standards. In the plugged condition they achieve IP 67 class of protection. The outlet direction is also a decisive factor: Weidmüller can also supply 0° versions, i.e. the cable outlet direction is located at the PE contact.

General ordering data

Version	, Straight plug - valve plug	
Order No.	<u>1316551000</u>	
Туре	SAIL-VSA-DS-M12G-10U	
GTIN (EAN)	4050118217346	
Qty.	1 pc(s).	



SAIL-VSA-DS-M12G-10U

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

ь.	-		
Dim	ensions	and	weights

Net weight	407 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical specifications for cable

5 m/s ²	Bending radius, min., moving	10 x cable diameter
5 x cable diameter	Cable length	10 m
blue, brown, Green/yellow, black, white	Core cross-section	0.34 mm²
No	Number of poles	4 (3 + PE)
Yes	Resistant to welding beads	No
PUR	Shielded	No
200 m/min	Suitable for cable carriers	Yes
-3090 °C	Temperature range, stationary	-4090 °C
360 °/m		
	5 x cable diameter blue, brown, Green/yellow, black, white No Yes PUR 200 m/min -3090 °C	5 x cable diameter blue, brown, Green/yellow, black, white No Yes PUR 200 m/min -3090 °C Cable length Core cross-section Number of poles Resistant to welding beads Shielded Suitable for cable carriers Temperature range, stationary

General technical data

Coding	Design A (18 mm), M12 =	Housing main material	
ŭ	Α	, and the second	TPU
LED	Yes	Plugging cycles	≥ 100
Pollution severity	3	Protection degree	IP67, when screwed in
Rated current	4 A	Rated voltage	24 V
Temperature range of housing	-25+80 °C	Version	Straight plug - valve plug

Classifications

ETIM 6.0	EC001855	ETIM 7.0	EC001855
ECLASS 9.0	27-06-03-12	ECLASS 9.1	27-06-03-11
ECLASS 10.0	27-06-03-12	ECLASS 11.0	27-06-03-12

Approvals

ROHS Conform

Downloads

Brochure/Catalogue <u>Catalogues in PDF-format</u>



SAIL-VSA-DS-M12G-10U


Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany


www.weidmueller.com

Drawings


Dimensioned drawing




Dimensioned drawing



Pole scheme



Pole scheme



Wiring

