

QVS 2/4 SAKT4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

QVS4 030740

Similar to illustration

Current and voltage transformer wiring

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General ordering data

Version	SAK Series, Cross-connector, Cross-connector, Number of poles: 2
Order No.	1319260000
Type	QVS 2/4 SAKT4
GTIN (EAN)	4008190136512
Qty.	20 pc(s).

QVS 2/4 SAKT4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	10.5 mm	Depth (inches)	0.413 inch
Height	22.3 mm	Height (inches)	0.878 inch
Net weight	0.767 g	Width	11 mm
Width (inches)	0.433 inch		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	100 °C		

Material data

Material	PA 66	Colour	beige
UL 94 flammability rating	V-2		

System specifications

Version	Cross-connector
---------	-----------------

Additional technical data

Explosion-tested version	No	Type of fixing	when screwed in
Type of mounting	Clamped		

Dimensions

Pitch in mm (P)	12 mm	TS 35 offset	45.5 mm
-----------------	-------	--------------	---------

General

Number of poles	2	Operating temperature range, max.	100 °C
-----------------	---	-----------------------------------	--------

Classifications

ETIM 6.0	EC000489	ETIM 7.0	EC000489
ECLASS 9.0	27-14-11-40	ECLASS 9.1	27-14-11-40
ECLASS 10.0	27-14-11-40	ECLASS 11.0	27-14-11-40

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	EAC certificate
Engineering Data	STEP
Engineering Data	EPLAN
User Documentation	StorageConditionsTerminalBlocks