

UC20-WL2000-AC**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

For modern IoT applications, automation technology needs to be increasingly more powerful and adaptable. u-mation offers a coordinated hardware portfolio designed for the future-proof preparation of your machines and systems. u-control 2000 is one of the most compact and state-of-the-art control systems on the market and is the centrepiece of our hardware portfolio. u-control 2000 forms the basis required for use of our engineering solutions u-create web, studio and IoT. The controllers modular design is based on the remote I/O system u-remote, and allows for needs-based expansion to include other components from the u-mation family.

General ordering data

Version	Controller, IP20, AutomationController, Web-based, u-control 2000 web, integrated engineering tool: u-create web for PLC - (real-time system) & IIoT applications
Order No.	1334950000
Type	UC20-WL2000-AC
GTIN (EAN)	4050118138351
Qty.	1 pc(s).

Creation date April 15, 2021 1:50:10 PM CEST

Catalogue status 09.04.2021 / We reserve the right to make technical changes.

UC20-WL2000-AC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	76 mm	Depth (inches)	2.992 inch
Height	120 mm	Height (inches)	4.724 inch
Mounting dimension - height	128 mm	Net weight	232 g
Width	52 mm	Width (inches)	2.047 inch

Connection data

Type of connection	PUSH IN
--------------------	---------

General data

Rail	TS 35	UL 94 flammability rating	V-0
------	-------	---------------------------	-----

Power supply

Current consumption from I _{IN} (power segment of the field bus coupler), typ.	116 mA	
Current consumption from I _{IN} (power segment of the fieldbus coupler), typ.	min.	0 mA
	max.	116 mA
	nominal	116 mA
Feed current for I _{IN} (input current path)	min.	0 mA
	max.	5,000 mA
	nominal	5,000 mA
Feed current for I _{IN} (input current path) , max.	5 A	
Feed current for I _{OUT} (output current path)	min.	0 mA
	max.	5,000 mA
	nominal	5,000 mA
Feed current for I _{OUT} (output current path) , max.	5 A	
Supply voltage for outputs	24 V DC +20 %/ -15 %	
Supply voltage system and inputs	24 V DC +20 %/ -15 %	

System data

Configuration interface	Micro USB 2.0	Connection type	2 x RJ45 plug-in connectors
Engineering tool	u-create web	Interface	2x Ethernet TCP/IP, 1x Micro USB
Memory (Flash)	4 GB, 32 GB via microSD	Module type	Controller
Processor	Dual Core ARM Cortex A9, 624 MHz, 512 Mbyte RAM	Programming environment	web-based
Real-time clock	Battery buffered	Transmission speed backplane bus, max.	48 Mbit
max. number of modules	64		

Classifications

ETIM 6.0	EC000236	ETIM 7.0	EC000236
ECLASS 9.0	27-24-22-07	ECLASS 9.1	27-24-22-07
ECLASS 10.0	27-24-22-07	ECLASS 11.0	27-24-22-07

UC20-WL2000-AC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS	Conform
UL File Number Search	E141197

Downloads

Approval/Certificate/Document of Conformity	UC20-WL2000-AC
Engineering Data	STEP
Product Change Notification	Release Notes - web
Software	u-link VPN-Client - Version 2.0.194 Current Firmware Archived Firmware
User Documentation	u-link Technical User Guide u-control Handbuch (Deutsch) u-control Manual (English) UC20-WL2000-AC Supported Modules List uc-documentation-UC20-WL2000-AC-X.XX
Brochure/Catalogue	Catalogues in PDF-format

UC20-WL2000-AC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Connection diagram

