

SAIE-M12S-8S0.5U HW**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Various build-in connectors are required for the connections on the device side of the sensor/actuator cabling. These are available in the versions M12, M8 and M5.

General ordering data

Version	Built-in plugs, M12, PG 9, Number of poles: 8
Order No.	1341240050
Type	SAIE-M12S-8S0.5U HW
GTIN (EAN)	4050118145717
Qty.	1 pc(s).

SAIE-M12S-8S0.5U HW**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	46 g
------------	------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data customisable plug-in connectors

Cable glands	PG 9	Contact surface	Gold-plated
Housing main material	Zinc diecast, nickel-plated	Number of poles	8
Plugging cycles	≥ 100	Protection degree	IP68
Rated current	2 A	Rated current	4 A (5-pole), 2 A (8-pole)
Rated voltage	60 V	Rated voltage (text)	125 V (5-pole) / 60 V (8-pole)
Temperature range of housing	-5 ... +70 °C	Type of connection	Pin

Classifications

ETIM 6.0	EC002635	ETIM 7.0	EC003570
ECLASS 9.0	27-44-01-03	ECLASS 9.1	27-44-01-03
ECLASS 10.0	27-44-01-03	ECLASS 11.0	27-44-01-03

Approvals

Approvals



ROHS

Conform


SAIE-M12S-8S0.5U HW

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Wiring diagram



Pole scheme

