

**PAC-UNIV-HE50-F-5M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Similar to illustration

**General ordering data**

|                 |                            |
|-----------------|----------------------------|
| Version         | Pre-assembled cable, PAC   |
| Order No.       | <a href="#">1349900050</a> |
| Type            | PAC-UNIV-HE50-F-5M         |
| GTIN (EAN)      | 4032248186549              |
| Qty.            | 1 pc(s).                   |
| Available until | 2014-05-20                 |

Creation date March 23, 2021 5:26:57 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**PAC-UNIV-HE50-F-5M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |       |
|------------|-------|
| Net weight | 590 g |
|------------|-------|

**Temperatures**

|                     |             |                       |             |
|---------------------|-------------|-----------------------|-------------|
| Storage temperature | -10...60 °C | Operating temperature | -10...50 °C |
|---------------------|-------------|-----------------------|-------------|

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**General Data**

|                    |                                          |                       |                 |
|--------------------|------------------------------------------|-----------------------|-----------------|
| Cable              | Cable LiYY                               | Cable length          | 5 m             |
| Connector PLC side | H0.14/10 (FERRULES 0.14mm <sup>2</sup> ) | Interface connector   | HE10 50 P       |
| Material           | PVC                                      | Number of poles, min. | 50-pole         |
| Outer diameter     | 13.4 ± 1 mm                              | Suitable for          | Digital signals |
| Wire cross-section | 0.14 mm <sup>2</sup>                     |                       |                 |

**Electrical Data**

|                        |                     |                                             |           |
|------------------------|---------------------|---------------------------------------------|-----------|
| Capacity wire / shield | 300 pF/m            | Capacity wire / wires                       | 300 pF/m  |
| Operating voltage      | ≤ 60 V DC ≤ 25 V AC | Permissible current strength per path, max. | 1 A       |
| Rated voltage (text)   | ≤ 60 V DC ≤ 25 V AC | Resistance                                  | ≤ 150mΩ/m |
| Total current, max.    | 3 A                 |                                             |           |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000237    | ETIM 7.0    | EC000237    |
| ECLASS 9.0  | 27-24-22-20 | ECLASS 9.1  | 27-24-22-20 |
| ECLASS 10.0 | 27-24-22-20 | ECLASS 11.0 | 27-24-22-20 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                               |
|--------------------|-------------------------------|
| User Documentation | <a href="#">Colours chart</a> |
|--------------------|-------------------------------|