

VPU I 2+0 R PV 600V DC**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

Type II surge voltage arrester for use in photovoltaic applications

- Pluggable arrester
- Suitable for protecting DC systems
- High energy absorption with short response time
- Tested in accordance with EN 50539-11
- Suitable for use in accordance with IEC 60364-7-712 / EN 50539-12
- Coded voltage level
- Installation in distribution board
- Thermal protection function

General ordering data

Version	Surge voltage arrester, Low voltage, 600 V, with remote contact
Order No.	1351490000
Type	VPU I 2+0 R PV 600V DC
GTIN (EAN)	4050118158625
Qty.	1 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2018-12-31

Creation date March 23, 2021 5:40:45 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

VPU I 2+0 R PV 600V DC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	69 mm	Depth (inches)	2.717 inch
Height	106 mm	Height (inches)	4.173 inch
Mounting dimension - height	75 mm	Net weight	494 g
Width	71.2 mm	Width (inches)	2.803 inch

Temperatures

Storage temperature	-40 °C...80 °C
---------------------	----------------

Connection data, remote alert

Connection type	PUSH IN	Cross-section for connected wire, solid core, max.	1.5 mm ²
Cross-section for connected wire, solid core, min.	0.14 mm ²	Stripping length	8 mm

General data

Colour	black	Design	Installation housing; 4TE, Insta IP 20
Optical function display	green = OK; red = arrester is defective - replace	Protection degree	IP20
Rail	TS 35	UL 94 flammability rating	V-0
Version	with remote contact		

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	IV
--------------------	---	------------------------	----

Photovoltaic technical data

Conditions and requirements	EN 50539-11	Maximum continuous operating voltage UCPV mode +/-, -/PE, +/-PE	600 V DC
PV system voltage, max. U _{cpv}	600 V	Protection level U _p mode (+/-)	≤ 3.6 kV
Protection level U _p mode (-/PE)	≤ 1.8 kV	Protection level U _p mode(+/-PE)	≤ 1.8 kV
Short-circuit current I _{scpv}	200 A	Standards	EN 50539-11

Rated data IEC / EN

Discharge current I _{max} (8/20μs) wire-PE	40 kA	Discharge current I _n (8/20μs) wire-PE	40 kA
Leakage current at U _n	100 μA	Lightning test current I _{imp} (10/350 μs) (L-PE)	12.5 kA
Max. continuous voltage, U _c (DC)	600 V	Number of poles	4
PV voltage, acc. to IEC 60364-7-712	< 600 V	Rated voltage (DC)	600 V
Response time	≤ 25 ns	SPD type	T1, T2
Signalling contact	250 V 1A 1CO, 125 V AC / 1 A, 48 V CC / 0.5 A, 24 V DC / 0.5 A	Standards	EN 50539-11
Voltage type	DC		

VPU I 2+0 R PV 600V DC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Connection data

Type of connection	Screw connection	Stripping length, rated connection	15 mm
Tightening torque, min.	2 Nm	Tightening torque, max.	3 Nm
Clamping range, rated connection	16 mm ²	Clamping range, min.	4 mm ²
Clamping range, max.	35 mm ²	Wire cross-section, solid, min.	2.5 mm ²
Wire cross-section, solid, max.	16 mm ²	Wire connection cross section, finely stranded, min.	2.5 mm ²
Wire connection cross section, finely stranded, max.	25 mm ²	Conductor cross-section, flexible, AEH (DIN 46228-1), min.	2.5 mm ²
Conductor cross-section, flexible, AEH (DIN 46228-1), max.	50 mm ²	Connection cross-section, stranded, min.	2.5 mm ²
Connection cross-section, stranded, max.	50 mm ²		

Classifications

ETIM 6.0	EC000941	ETIM 7.0	EC000941
ECLASS 9.0	27-13-08-05	ECLASS 9.1	27-13-08-05
ECLASS 10.0	27-13-08-05	ECLASS 11.0	27-13-08-05

Tender specification sheets

Long specification	Multi-pole surge voltage arrester according to the requirements of Class I acc. to IEC 50539-11. Consisting of V0 material, the arrester provides overvoltage protection in applications acc. to IEC 50539-12 in unearthed PV systems. The WEMID V0 arrester is installed in the vicinity of the equipment that needs protection, in a commercially available installation/electrical distribution enclosure. With thermal separation device on the varistor. If protection is no longer available, the colour in the display window changes from green to red. The functional state is also displayed by a voltage-free signalling contact (CO contact). Rated voltage: 600 VDC limp: 12.5 kA In/max (8/20 µs): 20/40 kA protection level < 1.8 kV telecommunication output: contact: 250 V/0.5 A 48 VDC/0.1 A Type: Weidmüller VPU I 2+0 R PV 600 V Order No. 135 14900000 or equivalent	Short specification Class I arrester with limp: 12.5 kA suitable for PV systems. Protection level < 1.8 kV. With remote alert Type: Weidmüller VPU I 2+0 R PV 600 V/12.5 kA Order no. 135 14900000 or equivalent
--------------------	--	---

VPU I 2+0 R PV 600V DC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	EAC VPU SERIES CE PAPER Declaration of Conformity
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD
User Documentation	Instruction sheet


VPU I 2+0 R PV 600V DC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Electric symbol



Circuit diagram