

IE-CC-NM-RPSMAM-2M**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

- For usage with the Weidmüller WLAN Access Point
- Omni-directional and planar antennas
- For use in the 2.4 GHz and 5 GHz band
- Open-air use possible thanks to the robust design (up to IP68)
- Cable for connecting external antennas to the Weidmüller WLAN Access Point in 2-metre and 4-metre versions

General ordering data

Version	Antenna cable, Connection 1:, N-type male, Connection 2:, RP-SMA male, Length: 2 m
Order No.	1367110000
Type	IE-CC-NM-RPSMAM-2M
GTIN (EAN)	4050118186376
Qty.	1 pc(s).

IE-CC-NM-RPSMAM-2M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	2 m	Length (inches)	78.74 inch
Net weight	152.68 g		

Temperatures

Operating temperature	-40 °C...85 °C
-----------------------	----------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Electrical properties of cable

Attenuation at 2.4 GHz	approx. 0.55 dB/m	Attenuation at 5 GHz	approx. 0.87 dB/m
Characteristic impedance	50 Ohm +/- 2	Max. operating frequency	6 Ghz
Signal propagation time	4.08 ns/m		

Mechanical and material properties of cable

Halogen	No, halogen-free, according to IEC 60754	Material sheath	LSFH (modified polyethylene)
Min. bending radius, once only	28 mm	Min. bending radius, repetitive	58 mm (for max. 50 bending cycles)
Sheath diameter	5.7 mm	Sheathing colour	black (similar to RAL 9005)
UV-resistant	ISO 4892-2A		

Technical data

Type of connection	Connection 1:, N-type male, Connection 2:, RP-SMA male
--------------------	--

Environmental conditions

Operating temperature, max.	85 °C	Operating temperature, min.	-40 °C
-----------------------------	-------	-----------------------------	--------

Classifications

ETIM 6.0	EC001682	ETIM 7.0	EC001682
ECLASS 9.0	27-06-03-10	ECLASS 9.1	27-06-03-10
ECLASS 10.0	27-06-03-10	ECLASS 11.0	27-06-03-10

Approvals

Approvals



ROHS	Conform
------	---------