

**KLIPPON COPL 121209****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

The Klippon® POK enclosure range is made from a high-quality glass fibre reinforced polyester and is ideal for applications and environments where corrosion resistance, impact resistance and a high IP protection class are a requirement.

Key features of the extensive product range:

- Available in 17 sizes
- Two standard finishes (colours): grey (similar to RAL 7001 for industrial use) and black (similar to RAL 9011 for harsh environments, Ex)
- Cover with stainless steel screws in cross-head / slotted design
- Moulded gasket made of silicone or chloroprene
- Fixing holes outside the sealed area to ensure high ingress protection of IP66
- Impact resistance up to 7 Joules
- Mounting directly in the enclosure or using an internal mounting plate
- Direct wall mounting possible using fixing holes or mounting feet
- Fastening thread to attach mounting rails and plates
- 
- Weidmüller can manufacture and supply this enclosure to match customer specifications - fitted with all necessary terminals and cable glands.

**General ordering data**

|            |                                                                                                                               |
|------------|-------------------------------------------------------------------------------------------------------------------------------|
| Version    | Klippon POK (polyester empty enclosure), Earthing plate, Height: 57.5 mm, Width: 177 mm, Material: Brass, polished, untreated |
| Order No.  | <a href="#">1390970000</a>                                                                                                    |
| Type       | KLIPPON COPL 121209                                                                                                           |
| GTIN (EAN) | 4050118191127                                                                                                                 |
| Qty.       | 1 pc(s).                                                                                                                      |

**KLIPPON COPL 121209****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                      |            |                      |            |
|----------------------|------------|----------------------|------------|
| Height               | 57.5 mm    | Height (inches)      | 2.264 inch |
| Net weight           | 64.77 g    | Wall thickness, max. | 0.8 mm     |
| Wall thickness, min. | 0.8 mm     | Width                | 177 mm     |
| Width (inches)       | 6.968 inch |                      |            |

**Certificate numbers enclosure**

|                       |                     |
|-----------------------|---------------------|
| Certificate No. (EAC) | RUC-DE.BE02.B.00173 |
|-----------------------|---------------------|

**General information**

|                |                     |                    |        |
|----------------|---------------------|--------------------|--------|
| Material       | Brass               | Material thickness | 0.8 mm |
| Surface finish | polished, untreated |                    |        |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002623    | ETIM 7.0    | EC002623    |
| ECLASS 9.0  | 27-18-28-14 | ECLASS 9.1  | 27-18-92-64 |
| ECLASS 10.0 | 27-18-28-14 | ECLASS 11.0 | 27-18-28-14 |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                              |
|------------------|------------------------------|
| Engineering Data | <a href="#">STEP</a>         |
| Engineering Data | <a href="#">EPLAN, WSCAD</a> |