

# Barb fitting CRCN-1/4-PK-4

Part number: 13972

FESTO



 General operating condition

## Data sheet

| Feature                                         | Value                                                              |
|-------------------------------------------------|--------------------------------------------------------------------|
| Nominal width                                   | 3.2 mm                                                             |
| Type of seal on screwed plug                    | Sealing ring                                                       |
| Pack size                                       | 1                                                                  |
| Operating pressure for entire temperature range | -0.95 bar ... 10 bar                                               |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7:-:-]                      |
| Information on operating and pilot media        | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)                | 2 - Moderate corrosion stress                                      |
| LABS (PWIS) conformity                          | VDMA24364-B2-L                                                     |
| For use in the food industry                    | See supplementary material information                             |
| Ambient temperature                             | 0 °C ... 60 °C                                                     |
| Product weight                                  | 17.73 g                                                            |
| Pneumatic connection 1                          | External thread G1/4                                               |
| Pneumatic connection 2                          | for pneumatic tubing outside diameter 6 mm                         |
| Note on materials                               | RoHS-compliant                                                     |
| Housing material                                | High-alloy stainless steel                                         |
| Material of threaded seal                       | PA-reinforced<br>TPE-U(PU)                                         |