

IE-FPOD2UG-MW

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Bulk stock, FO cable, POF

General ordering data

Version	Dragline cable, Break-out dragline, 980 µm, PUR, Products sold by meter, from 50 m
Order No.	1398770000
Type	IE-FPOD2UG-MW
GTIN (EAN)	4050118200614
Qty.	1 m
Delivery status	This article will no longer be available in the future.
Available until	2021-01-31

Creation date March 23, 2021 8:51:10 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-FPOD2UG-MW

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	46 g
------------	------

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-40 °C...85 °C
Installation temperature	-30 °C...60 °C		

Technical specifications for cable

Bending cycles	6 Mio	Colour coding	orange, black
Halogen	No	Number of wires	2
Sheathing colour	green		

Cable structure

Cable layout	Break-out dragline	Colour coding	orange, black
Core diameter	980 µm	Diameter of wire pair	2.2 mm
Material sheath	PUR	Number of wires	2
Primary coating	245 µm	Sheath diameter	7,5 mm
Sheath diameter, max.	8 mm	Sheathing colour	green
Tensile force, max.	1,000 N		

Mechanical and material properties of cable

Bending cycles	6 Mio	Bending cycles according to EN 60794-1-2-E8	r = 160 mm / 2 kg / 0.4 m/s
Colour	green	Halogen	No
Min. bending radius, once only	25 mm	Min. bending radius, repetitive	60 mm

Classifications

ETIM 6.0	EC000034	ETIM 7.0	EC000034
ECLASS 9.0	27-06-18-03	ECLASS 9.1	27-06-90-90
ECLASS 10.0	27-06-18-03	ECLASS 11.0	27-06-18-03

Approvals

ROHS	Conform
------	---------

Downloads

User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN
--------------------	--

IE-FPOD2UG-MW

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Detailed drawing

