



Main

Range of product	Modicon Quantum automation platform
Product or component type	Unity processor

Complementary

Mode of transmission	Multi mode
Clock frequency	266 MHz
Number of slots	10 16 2 4 6
Number of racks	2 - local rack(s)
Number of distributed I/O station	63 station(s) - 1 rack(s) - 3 Modbus Plus network(s)
Number of remote I/O station	0 - 0 S908 remote I/O rack(s) 6 - 2 ethernet X80 remote I/O rack(s) 0 - 0 ethernet Quantum remote I/O rack(s)
Discrete I/O number	0 - local - forbidden in Hot Standby application Up to 6 drops X80 - ethernet remote I/O 0 - S908 remote I/O - not configurable 8000 inputs, 8000 outputs - distributed - per network Modbus Plus
Analogue I/O number	0 - local - forbidden in Hot Standby application Up to 6 drops X80 - ethernet remote I/O 0 - S908 remote I/O - not configurable 500 inputs, 500 outputs - distributed - per network Modbus Plus
Application specific I/O	Accurate time stamping Counter High-speed interrupt inputs Serial link
Communication service	Ethernet router
Number of optional modules	3 (Ethernet, Modbus, Modbus Plus, Profibus DP, Sy/Max)
Maximum number of connections	3 (Profibus DP) - local 3 (Modbus Plus) - local 3 (Ethernet TCP/IP) - local 1 (Modbus) - RS232/485 Modbus/ASCII 4 (AS-Interface) - remote 2 (AS-Interface) - distributed 1 (USB)
Integrated connection type	1 optic fibre with Hot Standby protocol 1 USB with 1 Modbus with 1 Modbus Plus with
Checks	Hot standby Process control

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Memory description	Internal RAM 512 kB - 512 kB for data Expandable 8 MB - file storage with PCMCIA card Expandable 7168 kB - program with PCMCIA card
Switch function	Key switch memory port on/off
Application structure	1 cyclic/periodic master task - 4 auxiliary tasks - forbidden in Hot Standby application 32 timer interrupt tasks - forbidden in Hot Standby application 128 interrupt tasks - forbidden in Hot Standby application 128 I/O interrupt tasks - forbidden in Hot Standby application 1 periodic fast task - forbidden in Hot Standby application
Execution time per instruction	0.4...0.5 μ s floating points 0.0525...0.075 μ s Boolean 0.045...0.06 μ s on word 0.045...0.06 μ s on fixed-point arithmetic
Number of instructions per ms	20 Kinst/ms if 100 % Boolean 15 Kinst/ms if 65 % Boolean and 35 % numerical
System overhead	1 ms - master task 0.2 ms - fast task
Bus current requirement	2500 mA
Local signalling	1 LED red for Ethernet collision 1 LED green for Ethernet activity (COM)
Electrical connection	1 connector, connector type: MT-RJ (multimode fiber optic) for interconnecting primary and secondary PLCs up to 4 km 1 connector, connector type: RJ45 for connecting Modbus bus 1 female connector, connector type: SUB-D 9 for connecting to the Modbus Plus network

Environment


Product certifications	CE CSA GOST UL Misc (Marine)
Standards	HazLoc

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1111 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Racks for Modules Mounting

Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots