

THM WO VIN 25.4/95.2 BL**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

THM WriteOn cable markers on reels are used for labelling conductors and cables with an outside diameter of up to 36 mm. The transparent adhesive strip fixes and protects the printing on the marker surface.

- Protection of the marking against dirt and abrasion by wrapping it with the transparent adhesive strip
- Simple and quick printing with the high-quality thermal transfer printers

General ordering data

Version	THM, Conductor and cable markers, 12.7 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, white / yellow
Order No.	1420020000
Type	THM WO VIN 25.4/95.2 BL
GTIN (EAN)	4050118223514
Qty.	1 pc(s).

Creation date March 23, 2021 10:01:29 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

THM WO VIN 25.4/95.2 BL

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	0.065 mm	Depth (inches)	0.003 inch
Height	25.4 mm	Height (inches)	1 inch
Net weight	545 g	Width	95.3 mm
Width (inches)	3.752 inch		

Temperatures

Operating temperature range	-40...80 °C
-----------------------------	-------------

General data

Adhesive	Polyacrylate adhesive	Approval acc. to UL 969	No
Colour	white / yellow	Halogen	Yes
Material	Vinyl film	Number of markers per combination	1 Label reel = Conductor and cable markers
Number per roll	1,000	Operating temperature range	-40...80 °C
Operating temperature range, max.	80 °C	Operating temperature range, min.	-40 °C
Printing	Lightning	Size of labelling field	40 x 25.4 mm
UL 94 flammability rating	V-0	Version	Self-adhesive
Width	95.3 mm		

Conductor and cable markers

Conductor O.D.	12.7 mm	Conductor O.D., max.	12.7 mm
Conductor cross-section, max.	120 mm ²	Conductor cross-section, min.	0.75 mm ²
Cross-section for connected wire	0.75 - 120 mm ²	Halogen	Yes

Classifications

ETIM 6.0	EC001530	ETIM 7.0	EC001530
ECLASS 9.0	27-40-04-01	ECLASS 9.1	27-40-04-01
ECLASS 10.0	27-40-04-01	ECLASS 11.0	27-28-11-02

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD

THM WO VIN 25.4/95.2 BL

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

