

**HSS-HF 19.1-38.1EL Y10M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The heat-shrinkable sleeve is printable on 2 sides and can be used for marking and insulating cables and wires. The flexible, heat-shrink material enables a firm, perfect fit around the conductor and therefore saves space.

**General ordering data**

|                    |                                                                                                                       |
|--------------------|-----------------------------------------------------------------------------------------------------------------------|
| Version            | Conductor and cable markers, 19.1 - 38.1 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, yellow |
| Order No.          | <a href="#">1423310000</a>                                                                                            |
| Type               | HSS-HF 19.1-38.1EL Y10M                                                                                               |
| GTIN (EAN)         | 4050118227765                                                                                                         |
| Qty.               | 1 pc(s).                                                                                                              |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a> <a href="#">1140490000</a>                                      |

Creation date March 23, 2021 10:08:35 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**HSS-HF 19.1-38.1EL Y10M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 1.5 mm     | Depth (inches)  | 0.059 inch |
| Length         | 10,000 mm  | Length (inches) | 393.7 inch |
| Net weight     | 936 g      | Width           | 60.5 mm    |
| Width (inches) | 2.382 inch |                 |            |

**Temperatures**

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -55...105 °C |
|-----------------------------|--------------|

**General data**

|                                   |                |                                   |              |
|-----------------------------------|----------------|-----------------------------------|--------------|
| Colour                            | yellow         | Halogen                           | No           |
| Length                            | 10,000 mm      | Material                          | Polyolefine  |
| Number per roll                   | 1              | Operating temperature range       | -55...105 °C |
| Operating temperature range, max. | 105 °C         | Operating temperature range, min. | -55 °C       |
| Recommended industries            | Transportation | Width                             | 60.5 mm      |

**Conductor and cable markers**

|                                   |                    |                                  |                          |
|-----------------------------------|--------------------|----------------------------------|--------------------------|
| Conductor O.D.                    | 19.1 - 38.1 mm     | Conductor O.D., max.             | 38.1 mm                  |
| Conductor O.D., min.              | 19.1 mm            | Conductor cross-section, max.    | 240 mm <sup>2</sup>      |
| Conductor cross-section, min.     | 70 mm <sup>2</sup> | Cross-section for connected wire | 70 - 240 mm <sup>2</sup> |
| Halogen                           | No                 | Rate of shrinkage                | 2:1                      |
| Recommended shrinking temperature | 90 °C              |                                  |                          |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                                             |                                                                                                                                               |
|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">NFX 70-100-1 2006 + NF X 70-100-2 2006</a><br><a href="#">BS EN 45545-2 2013+A1 2015</a><br><a href="#">BS EN ISO 4589-2 1999</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD</a>                                                                                                                  |

**HSS-HF 19.1-38.1EL Y10M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

---

---

---