

## CC DIA 30/3.5 MC NE RT


**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



ClipCard device markers in MultiCard format are used for labelling electrical installations and switchgear systems, and offer an interesting alternative to engraving. Thanks to the proven MultiCard format, labelling is possible with PrintJet CONNECT or Plotter.

- Highly resistant printing quality when using the PrintJet as a substitute for engraving
- Universal fixing
- Carrier (screwable or with cable ties)
- Tag rail (self-adhesive or screw fixing)
- Or self-adhesive tags

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### General ordering data

|                     |                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------|
| Version             | ClipCard, Device markers, {Reference (AttributeDefinition) not found: pAttr74196859207437}, With hole, red |
| Order No.           | <a href="#">1434110000</a>                                                                                 |
| Type                | CC DIA 30/3.5 MC NE RT                                                                                     |
| GTIN (EAN)          | 4050118238723                                                                                              |
| Qty.                | 60 pc(s).                                                                                                  |
| Alternative product | <a href="#">1266150000</a>                                                                                 |
| compatible printer  | <a href="#">2715590000</a> <a href="#">2438520000</a> <a href="#">2438510000</a>                           |

Creation date March 23, 2021 10:44:48 PM CET

## CC DIA 30/3.5 MC NE RT

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                 |            |                |            |
|-----------------|------------|----------------|------------|
| Depth           | 1.2 mm     | Depth (inches) | 0.047 inch |
| Diameter        | 30 mm      | Height         | 30 mm      |
| Height (inches) | 1.181 inch | Net weight     | 2.15 g     |
| Width           | 30 mm      | Width (inches) | 1.181 inch |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -40...100 °C |
|-----------------------------|--------------|

## General data

|                                   |                                    |                                   |              |
|-----------------------------------|------------------------------------|-----------------------------------|--------------|
| Application/manufacture           | With hole                          | Colour                            | red          |
| Halogen                           | No                                 | Material                          | Polyamide 66 |
| Number of markers per combination | 1 MultiCard = Device markers       | Operating temperature range       | -40...100 °C |
| Operating temperature range, max. | 100 °C                             | Operating temperature range, min. | -40 °C       |
| Recommended industries            | Machinery                          | UL 94 flammability rating         | V-2          |
| Version                           | Ø 30 mm, with 3.5 mm mounting hole | Width                             | 30 mm        |

## Device markers

|          |       |                     |        |
|----------|-------|---------------------|--------|
| Diameter | 30 mm | Drill-hole diameter | 3.5 mm |
| Halogen  | No    |                     |        |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001288    | ETIM 7.0    | EC001288    |
| ECLASS 9.0  | 27-40-06-29 | ECLASS 9.1  | 27-40-06-29 |
| ECLASS 10.0 | 27-40-06-29 | ECLASS 11.0 | 27-28-11-04 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                             |                                                                                |
|-----------------------------|--------------------------------------------------------------------------------|
| Engineering Data            | <a href="#">STEP</a>                                                           |
| Engineering Data            | <a href="#">EPLAN, WSCAD</a>                                                   |
| Product Change Notification | <a href="#">Technical change - DE</a><br><a href="#">Technical change - EN</a> |

### CC DIA 30/3.5 MC NE RT

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

