

IE-FCI-PWB-FR**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

General ordering data

Version	FrontCom, Insert Power large, Type E, Socket connector, FR
Order No.	1450750000
Type	IE-FCI-PWB-FR
GTIN (EAN)	4050118255706
Qty.	1 pc(s).

IE-FCI-PWB-FR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight

29.708 g

Weight

29 g

Temperatures

Storage temperature

-10 °C...70 °C

Operating temperature

-5 °C...50 °C

General data

Connector face

Type E

Insert type

Insert Power large

Protection degree

IP20

Clampable conductors

Conductor connection cross-section,
extremely flexible with wire end ferrule1.5 ... 1.5 mm²Conductor connection cross-section,
extremely flexible with wire end ferrule

max.

1.5 mm²

min.

1.5 mm²Conductor connection cross-section,
extremely flexible without wire end
ferrule1.5 ... 2.5 mm²Conductor connection cross-section,
extremely flexible without wire end
ferrule

min.

1.5 mm²

max.

2.5 mm²Conductor connection cross-section,
flexible with wire end ferrule1.5 ... 1.5 mm²Conductor connection cross-section,
flexible with wire end ferrule

max.

1.5 mm²

min.

1.5 mm²Conductor connection cross-section,
flexible without wire end ferrule1.5 ... 2.5 mm²Conductor connection cross-section,
flexible without wire end ferrule

max.

2.5 mm²

min.

1.5 mm²Conductor connection cross-section,
rigid1.5 ... 2.5 mm²Conductor connection cross-section,
rigid

max.

2.5 mm²

min.

1.5 mm²

Stripping length

10 mm

Type of connection

PUSH IN

Technical data

Housing main material

Polycarbonate PC

Rated current

16 A

Rated voltage (AC)

250 V

General standards

Certificate No. (GERMLLOYD)

13866-15

Classifications

ETIM 6.0

EC001121

ETIM 7.0

EC001121

ECLASS 9.0

27-44-03-90

ECLASS 9.1

27-18-90-90

ECLASS 10.0

27-44-03-90

ECLASS 11.0

27-44-03-90

IE-FCI-PWB-FR**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Approvals**

Approvals



ROHS

Conform

DownloadsApproval/Certificate/Document of
Conformity[GL_FrontCom](#)

Engineering Data

[STEP](#)

User Documentation

[MAN IE GUIDE DE](#)[MAN IE GUIDE EN](#)[Socket Insert Overview EN](#)[Socket Insert Overview DE](#)[Designation key / Type key](#)


IE-FCI-PWB-FR

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensioned drawing



Dimensioned drawing

