

RS F20 X3 OUT**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The interfaces for redundancy are supplied with various IEC 60603-13 connectors. This enables various controllers to work in parallel, although not simultaneously, with the new system being tested.

General ordering data

Order No.	1461220000
Type	RS F20 X3 OUT
GTIN (EAN)	4050118266955
Qty.	1 pc(s).

RS F20 X3 OUT

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Height	50 mm	Height (inches)	1.969 inch
Length	65 mm	Length (inches)	2.559 inch
Net weight	75 g	Width	70 mm
Width (inches)	2.756 inch		

Temperatures

Storage temperature	-40...60 °C	Operating temperature	-25...50 °C
---------------------	-------------	-----------------------	-------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Connection Data

Connection on control side	3 x plug-in connectors in acc. with IEC60603-13 / DIN41651	Earthing	No
Number of poles (control side)	20-pole		

Rating data

Rated voltage	50 V AC / 70 V DC	Rated current per connection	0.5 A
Total operating current	3 A		

Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	50 V AC / 70 V DC
Surge voltage category	II	Pollution severity level	2
Insulation test voltage	0.35 kVAC		

Classifications

ETIM 6.0	EC002584	ETIM 7.0	EC002584
ECLASS 9.0	27-33-02-92	ECLASS 9.1	27-24-22-92
ECLASS 10.0	27-33-02-92	ECLASS 11.0	27-33-02-92

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	Declaration of Conformity
Engineering Data	EPLAN

RS F20 X3 OUT

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

