

CP A WALLADAPTER 45MM**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Due to the wide range of variants with output voltages of 5, 12, 24, and 48 V and extensive international approvals, they are suitable for use in many applications. The power range extends from 35 W to 350 W. The individual adaptability makes PRO-PM the right choice for many standard machines.

General ordering data

Version	
Order No.	1461850000
Type	CP A WALLADAPTER 45MM
GTIN (EAN)	4050118268010
Qty.	1 pc(s).

CP A WALLADAPTER 45MM**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Depth	3 mm	Depth (inches)	0.118 inch
Height	180 mm	Height (inches)	7.087 inch
Net weight	168 g	Width	45 mm
Width (inches)	1.772 inch		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Classifications

ETIM 6.0	EC002625	ETIM 7.0	EC002625
ECLASS 9.0	27-18-28-07	ECLASS 9.1	27-04-92-90
ECLASS 10.0	27-18-28-07	ECLASS 11.0	27-18-28-07

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN