

IE-CSQS9VE0015AQEAQE-K1**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Assembled IE cables

General ordering data

Version	System cable, V14 hybrid (shielded), V14 hybrid (shielded), PVC, 1.5 m, Hybrid
Order No.	1465850015
Type	IE-CSQS9VE0015AQEAQE-K1
GTIN (EAN)	4050118272345
Qty.	1 pc(s).

Creation date March 24, 2021 12:10:51 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-CSQS9VE0015AQEAQE-K1

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	1.5 m	Length (inches)	59.055 inch
Net weight	310 g		

Temperatures

Operating temperature	-40 °C...80 °C
-----------------------	----------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Electrical properties

Insulation strength	> 500 MΩ	Operating voltage	300 V
---------------------	----------	-------------------	-------

General standards

Connector standard	IEC 61076-3-119 CDV, IEC 61076-3-117 Var. 14
--------------------	--

Standards

Connector standard	IEC 61076-3-119 CDV, IEC 61076-3-117 Var. 14
--------------------	--

Cable structure

Cable layout	Hybrid cable, for permanent installation	Cross-section	2 x 0.34 mm ² + 7 x 0.5 mm ²
Insulation	PP	Insulation cross-section	1.25 mm
Insulation diameter 2	2.15 mm	Material sheath	PVC
Overlap of shielding braid	85 %	Sheath diameter, max.	9.5 mm
Sheath diameter, min.	9.1 mm	Sheathing colour	black

Electrical properties of cable

Insulation strength	> 500 MΩ	Operating voltage	300 V
---------------------	----------	-------------------	-------

Mechanical and material properties of cable

Min. bending radius, once only	5 x cable diameter	Min. bending radius, repetitive	10 x cable diameter
--------------------------------	--------------------	---------------------------------	---------------------

Plug, left

Connector left	V14 hybrid (shielded)
----------------	-----------------------

Plug, right

Connector right	V14 hybrid (shielded)
-----------------	-----------------------

plug

Connector left	V14 hybrid (shielded)	Connector right	V14 hybrid (shielded)
----------------	-----------------------	-----------------	-----------------------

IE-CSQS9VE0015AQEAQE-K1**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Classifications**

ETIM 6.0	EC001579	ETIM 7.0	EC001579
ECLASS 9.0	27-06-24-90	ECLASS 9.1	27-06-24-00
ECLASS 10.0	27-06-05-01	ECLASS 11.0	27-06-05-01

Approvals

Approvals



ROHS

Conform

Downloads

User Documentation

[MAN IE GUIDE DE](#)[MAN IE GUIDE EN](#)

IE-CSQS9VE0015AQEAQE-K1

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Wiring

