

**STRIPAX ULTIMATE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- Stripping tools with automatic self-adjustment
- For flexible and solid conductors
- Ideally suitable for mechanical and plant engineering, railway and rail traffic, wind energy, robot technology, explosion protection as well as marine, offshore and ship building sectors
- Stripping length adjustable via end stop
- Automatic opening of clamping jaws after stripping
- No fanning-out of individual conductors
- Adjustable to diverse insulation thicknesses
- Double-insulated cables in two process steps without special adjustment
- No play in self-adjusting cutting unit
- Long service life
- Optimised ergonomic design

**General ordering data**

|            |                                   |
|------------|-----------------------------------|
| Version    | Tools, Stripping and cutting tool |
| Order No.  | <a href="#">1468880000</a>        |
| Type       | STRIPAX ULTIMATE                  |
| GTIN (EAN) | 4050118274158                     |
| Qty.       | 1 pc(s).                          |

**STRIPAX ULTIMATE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 22 mm   | Depth (inches)  | 0.866 inch |
| Height     | 99 mm   | Height (inches) | 3.898 inch |
| Net weight | 221.4 g | Weight          | 222 g      |
| Width      | 190 mm  | Width (inches)  | 7.48 inch  |

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Technical data**

|                        |                    |
|------------------------|--------------------|
| Description of article | Wire stripper unit |
|------------------------|--------------------|

**Stripping tools**

|                               |                                                            |                                            |                      |
|-------------------------------|------------------------------------------------------------|--------------------------------------------|----------------------|
| Cable type                    | Flexible and solid conductors with halogen-free insulation | Conductor cross-section (cutting capacity) | 6 mm <sup>2</sup>    |
| Conductor cross-section, max. | 6 mm <sup>2</sup>                                          | Conductor cross-section, min.              | 0.25 mm <sup>2</sup> |
| Stripping length, max.        | 25 mm                                                      | Stripping range AWG, max.                  | 10 AWG               |
| Stripping range AWG, min.     | 24 AWG                                                     |                                            |                      |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002109    | ETIM 7.0    | EC002109    |
| ECLASS 9.0  | 21-04-37-06 | ECLASS 9.1  | 21-04-37-06 |
| ECLASS 10.0 | 21-04-37-06 | ECLASS 11.0 | 21-04-37-06 |

**Approvals**

Approvals

**Downloads**

|                    |                        |
|--------------------|------------------------|
| Engineering Data   | <a href="#">STEP</a>   |
| User Documentation | <a href="#">Manual</a> |

## STRIPAX ULTIMATE

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings



### Example of use



### Example of use



TYPE THHN

ALOGEN FREE 2,5MM<sup>2</sup> H07Z-K