

CC-M 85/54 ST SDR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







MetalliCards are available in aluminium or stainless steel to meet a wide range of labelling requirements. The chrome-coated aluminium tags are the inexpensive alternative for a variety of applications, and in particular, they prove themselves through the deep contrasts of their multi-colour print.

In the technologically demanding chemical and process industries, you are on the safe side when using the stainless steel MetalliCard with its outstanding resistance characteristics. Its formats cover the needs of the entire system-identification spectrum. Whether small equipment or type plates, they ensure high-quality marking processes. The MetalliCard also offers optimum installation characteristics. MetalliCards can be used universally thanks to various fixation options: bonding, riveting, with tag holders or rails, or in combination with stainless steel cable ties.

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| Version | MetalliCard, Device markers, {Reference | | |
|------------|---|--|--|
| | (AttributeDefinition) not found: | | |
| | pAttr74196859207437}, silver | | |
| Order No. | <u>1474060000</u> | | |
| Туре | CC-M 85/54 ST SDR | | |
| GTIN (EAN) | 4050118290325 | | |
| Qty. | 1 pc(s). | | |



CC-M 85/54 ST SDR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

| Depth | 0.5 mm | Depth (inches) | 0.02 inch |
|----------------|------------|-----------------|------------|
| Height | 54 mm | Height (inches) | 2.126 inch |
| Net weight | 17.4 g | Width | 85 mm |
| Width (inches) | 3.346 inch | | |

Temperatures

Operating temperature range -55...130 °C

General data

| Colour | silver | Material | Micro-etched stainless steel 1.4301 (ST) |
|-----------------------------------|---|-----------------------------------|--|
| Number of markers per combination | 1 MetalliCard = Device markers | Operating temperature range | -55130 °C |
| Operating temperature range, max. | 130 °C | Operating temperature range, min. | -55 °C |
| Printed characters | Based on customer requirements (Please send M-Print PRO file) | Size of labelling field | 83.8 x 52.4 mm |
| Width | 85 mm | | 03.0 X 32.4 IIIII |

Classifications

| ETIM 6.0 | EC001288 | ETIM 7.0 | EC001288 |
|-------------|-------------|-------------|-------------|
| ECLASS 9.0 | 27-40-06-29 | ECLASS 9.1 | 27-40-06-29 |
| ECLASS 10.0 | 27-40-06-29 | ECLASS 11.0 | 27-28-11-04 |

Approvals

ROHS Conform

Downloads

Engineering Data EPLAN, WSCAD



CC-M 85/54 ST SDR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Drawings

Example of use

