

**H0,75/14 W SP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Similar to illustration**

- supplied loose in polybag
- in multipack bag (5 x 100 pcs.)
- strip of wire end ferrules (50 pcs.)
- strip of wire end ferrules on reel (5,000 pcs.)
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |                                                 |
|------------|-------------------------------------------------|
| Version    | Wire-end ferrule, insulated, 10 mm, 8 mm, white |
| Order No.  | <a href="#">1476240000</a>                      |
| Type       | H0,75/14 W SP                                   |
| GTIN (EAN) | 4050118282894                                   |
| Qty.       | 100 pc(s).                                      |

**H0,75/14 W SP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |
|------------|---------|
| Net weight | 0.019 g |
|------------|---------|

**Technical data**

|                        |                                             |         |           |
|------------------------|---------------------------------------------|---------|-----------|
| Description of article | Wire end ferrule with plastic collar, white | Version | insulated |
|------------------------|---------------------------------------------|---------|-----------|

**Wire-end ferrules**

|                             |                      |                                         |            |
|-----------------------------|----------------------|-----------------------------------------|------------|
| Collar diameter (D2)        | 2.8 mm               | Colour code                             | Weidmüller |
| Conductor cross-section     | 0.75 mm <sup>2</sup> | Contact surface diameter (D1)           | 1.2 mm     |
| Contact surface length (L2) | 8 mm                 | L1 in mm                                | 14 mm      |
| Metal sleeve thickness (S1) | 0.15 mm              | Plastic collar thickness (S2)           | 0.25 mm    |
| Stripping length            | 10 mm                | Wire connection cross section AWG, max. | AWG 18     |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E499744 |

**Downloads**

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">EPLAN</a>                                                                    |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |

## H0,75/14 W SP

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

## Drawing

