



Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L
Length in 18 mm modules	22

Complementary

Number of ways	5 ways 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	27 mm
Connector type	Tooth
Distance between way	81 mm
Marking	L1 L2 L3
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	125 A at 40 °C
[Ue] rated operational voltage	500 V AC
[Ui] rated insulation voltage	620 V AC
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	45
Width	405 mm
Colour	Anthracite grey (RAL 7016)
Range compatibility	Acti 9 NG125 Acti 9 C120

Environment

Standards	IEC 60664-1
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------