

## B2L 3.50/18/180 SN OR BX PRT

**Weidmüller Interface GmbH & Co. KG**


Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

### Product image



### Component density redefined: the future standard for signal connection

A maximum number of connections requiring minimum space - the double-row B2L sets the bar for field connections of typical sensor cables up to 1 mm<sup>2</sup> very high and closes the gap between "less space" and "more functions".

The result is a connection solution for standard industrial cables in 1.75 pitch - 30% smaller than equivalent solutions in 2.5 pitch, and with the 140% robustness of the 3.5 pitch

Dimensions: double the connection density with a 3.5mm pitch size

Connection system: tried and tested maintenance-free Weidmüller tension clamp connection

The basic application advantages:

Efficient: maximum component density on the PCB

Suitable for industrial use - minimum dimensions, maximum robustness

Process-optimised - automatic assembly and reflow soldering, fast connection

User-friendly - patented release lever for the easy release of larger numbers of poles

Application-oriented: easy labelling and reliable coding despite compact dimensions

Miniaturisation is more than just a larger number of functions within a smaller space:

Each reduction in size decreases space requirements and so reduces overall system costs for the end customer. Thus, Weidmüller fulfils a growing demand in the engineering and industrial automation sectors.

### General ordering data

|              |                                                                                                                                                 |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Version      | PCB plug-in connector, female plug, 3.50 mm, Number of poles: 18, 180°, Tension-clamp connection, Clamping range, max.: 1 mm <sup>2</sup> , Box |
| Order No.    | <a href="#">1483210000</a>                                                                                                                      |
| Type         | B2L 3.50/18/180 SN OR BX PRT                                                                                                                    |
| GTIN (EAN)   | 4050118292398                                                                                                                                   |
| Qty.         | 54 pc(s).                                                                                                                                       |
| Product data | IEC: 200 V / 10.3 A / 0.2 - 1 mm <sup>2</sup><br>UL: 300 V / 10 A / AWG 28 - AWG 16                                                             |
| Packaging    | Box                                                                                                                                             |

Creation date April 15, 2021 3:49:50 PM CEST

**B2L 3.50/18/180 SN OR BX PRT****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|                |           |                 |            |
|----------------|-----------|-----------------|------------|
| Depth          | 20.8 mm   | Depth (inches)  | 0.819 inch |
| Height         | 15.7 mm   | Height (inches) | 0.618 inch |
| Net weight     | 9.218 g   | Width           | 31.5 mm    |
| Width (inches) | 1.24 inch |                 |            |

**System Parameters**

|                                              |                                               |                                            |                   |
|----------------------------------------------|-----------------------------------------------|--------------------------------------------|-------------------|
| Product family                               | OMNIMATE Signal - series B2L/S2L 3.50 - 2-row | Type of connection                         | Field connection  |
| Wire connection method                       | Tension-clamp connection                      | Pitch in mm (P)                            | 3.5 mm            |
| Pitch in inches (P)                          | 0.138 inch                                    | Conductor outlet direction                 | 180°              |
| Number of poles                              | 18                                            | L1 in mm                                   | 28 mm             |
| L1 in inches                                 | 1.102 inch                                    | Number of rows                             | 1                 |
| Pin series quantity                          | 2                                             | Rated cross-section                        | 1 mm <sup>2</sup> |
| Touch-safe protection acc. to DIN VDE 57 106 | Safe from finger touch                        | Touch-safe protection acc. to DIN VDE 0470 | IP 20             |
| Can be coded                                 | Yes                                           | Stripping length                           | 7 mm              |
| Screwdriver blade                            | 0.4 x 2.5                                     | Screwdriver blade standard                 | DIN 5264          |
| Plugging cycles                              | 25                                            | Plugging force/pole, max.                  | 5 N               |
| Pulling force/pole, max.                     | 4 N                                           |                                            |                   |

**Material data**

|                                       |          |                                       |                     |
|---------------------------------------|----------|---------------------------------------|---------------------|
| Insulating material                   | PBT      | Colour                                | orange              |
| Colour chart (similar)                | RAL 2000 | Insulation strength                   | ≥ 10 <sup>8</sup> Ω |
| UL 94 flammability rating             | V-0      | Contact material                      | Copper alloy        |
| Contact surface                       | tinned   | Storage temperature, min.             | -40 °C              |
| Storage temperature, max.             | 70 °C    | Operating temperature, min.           | -50 °C              |
| Operating temperature, max.           | 100 °C   | Temperature range, installation, min. | -30 °C              |
| Temperature range, installation, max. | 100 °C   |                                       |                     |

**Conductors suitable for connection**

|                                                 |                      |
|-------------------------------------------------|----------------------|
| Clamping range, min.                            | 0.08 mm <sup>2</sup> |
| Clamping range, max.                            | 1 mm <sup>2</sup>    |
| Wire connection cross section AWG, min.         | AWG 28               |
| Wire connection cross section AWG, max.         | AWG 18               |
| Solid, min. H05(07) V-U                         | 0.2 mm <sup>2</sup>  |
| Solid, max. H05(07) V-U                         | 1 mm <sup>2</sup>    |
| Flexible, min. H05(07) V-K                      | 0.2 mm <sup>2</sup>  |
| Flexible, max. H05(07) V-K                      | 1 mm <sup>2</sup>    |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.14 mm <sup>2</sup> |
| w. plastic collar ferrule, DIN 46228 pt 4, max. | 0.34 mm <sup>2</sup> |
| w. wire end ferrule, DIN 46228 pt 1, min.       | 0.14 mm <sup>2</sup> |
| w. wire end ferrule, DIN 46228 pt 1, max.       | 0.34 mm <sup>2</sup> |

**B2L 3.50/18/180 SN OR BX PRT****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data**

|                     |                                                                                                                                                                        |                              |                                |       |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|--------------------------------|-------|
| Clampable conductor | Cross-section for conductor connection                                                                                                                                 | Type                         | fine-wired                     |       |
|                     |                                                                                                                                                                        | nominal                      | 0.14 mm²                       |       |
|                     | wire end ferrule                                                                                                                                                       | Stripping length             | nominal                        | 10 mm |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H0.14/12 GR SV</a> |       |
|                     | Cross-section for conductor connection                                                                                                                                 | Type                         | fine-wired                     |       |
|                     |                                                                                                                                                                        | nominal                      | 0.25 mm²                       |       |
|                     | wire end ferrule                                                                                                                                                       | Stripping length             | nominal                        | 10 mm |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H0.25/12 HBL</a>   |       |
| Reference text      | The outside diameter of the plastic collar should not be larger than the pitch (P). Length of ferrules is to be chosen depending on the product and the rated voltage. |                              |                                |       |

**Rated data acc. to IEC**

|                                                                           |                        |  |                                                                       |                  |
|---------------------------------------------------------------------------|------------------------|--|-----------------------------------------------------------------------|------------------|
| tested acc. to standard                                                   | IEC 60664-1, IEC 61984 |  | Rated current, min. number of poles (Tu=20°C)                         | 10.3 A           |
| Rated current, max. number of poles (Tu=20°C)                             | 8.7 A                  |  | Rated current, min. number of poles (Tu=40°C)                         | 8.9 A            |
| Rated current, max. number of poles (Tu=40°C)                             | 7.4 A                  |  | Rated voltage for surge voltage class / pollution degree II/2         | 200 V            |
| Rated voltage for surge voltage class / pollution degree III/2            | 160 V                  |  | Rated voltage for surge voltage class / pollution degree III/3        | 80 V             |
| Rated impulse voltage for surge voltage class/ pollution degree II/2      | 2.5 kV                 |  | Rated impulse voltage for surge voltage class/ pollution degree III/2 | 2.5 kV           |
| Rated impulse voltage for surge voltage class/ contamination degree III/3 | 2.5 kV                 |  | Short-time withstand current resistance                               | 3 x 1s with 77 A |

**Rated data acc. to CSA**

|                                   |        |                                   |        |
|-----------------------------------|--------|-----------------------------------|--------|
| Rated voltage (Use group B / CSA) | 300 V  | Rated current (Use group B / CSA) | 5 A    |
| Wire cross-section, AWG, min.     | AWG 28 | Wire cross-section, AWG, max.     | AWG 18 |

**Rated data acc. to UL 1059**

|                                       |                                                                                     |  |                                       |        |
|---------------------------------------|-------------------------------------------------------------------------------------|--|---------------------------------------|--------|
| Institute (UR)                        |  |  | Certificate No. (UR)                  | E60693 |
| Rated voltage (Use group B / UL 1059) | 300 V                                                                               |  | Rated voltage (Use group C / UL 1059) | 50 V   |
| Rated current (Use group B / UL 1059) | 10 A                                                                                |  | Rated current (Use group C / UL 1059) | 10 A   |
| Wire cross-section, AWG, min.         | AWG 28                                                                              |  | Wire cross-section, AWG, max.         | AWG 16 |
| Reference to approval values          | Specifications are maximum values, details - see approval certificate.              |  |                                       |        |

**Packing**

|           |        |            |        |
|-----------|--------|------------|--------|
| Packaging | Box    | VPE length | 338 mm |
| VPE width | 130 mm | VPE height | 27 mm  |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002638    | ETIM 7.0    | EC002638    |
| ECLASS 9.0  | 27-44-03-09 | ECLASS 9.1  | 27-44-03-09 |
| ECLASS 10.0 | 27-44-03-09 | ECLASS 11.0 | 27-46-02-02 |

**B2L 3.50/18/180 SN OR BX PRT****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Important note**

|                |                                                                                                                                                                                                                                                                                                                            |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request. |
| Notes          | <ul style="list-style-type: none"><li>Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months</li></ul>                                                                                                                                                                     |

**Approvals**

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E60693  |

**Downloads**

|                    |                                          |
|--------------------|------------------------------------------|
| Brochure/Catalogue | <a href="#">Catalogues in PDF-format</a> |
|--------------------|------------------------------------------|


## B2L 3.50/18/180 SN OR BX PRT

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany


[www.weidmueller.com](http://www.weidmueller.com)

# Drawings


## Dimensional drawing



## Graph



## Graph



## Graph

