

**HSS 6.4-19.1 EL W10M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The heat-shrinkable sleeve is printable on 2 sides and can be used for marking and insulating cables and wires. The flexible, heat-shrink material enables a firm, perfect fit around the conductor and therefore saves space.

**General ordering data**

|                    |                                                                                                                     |
|--------------------|---------------------------------------------------------------------------------------------------------------------|
| Version            | Conductor and cable markers, 6.4 - 19.1 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, white |
| Order No.          | <a href="#">1489680000</a>                                                                                          |
| Type               | HSS 6.4-19.1 EL W10M                                                                                                |
| GTIN (EAN)         | 4050118299366                                                                                                       |
| Qty.               | 1 pc(s).                                                                                                            |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a> <a href="#">1140490000</a>                                    |

Creation date March 24, 2021 1:48:08 AM CET

## HSS 6.4-19.1 EL W10M

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 0.77 mm    | Depth (inches)  | 0.03 inch  |
| Length         | 10,000 mm  | Length (inches) | 393.7 inch |
| Net weight     | 304 g      | Width           | 30.9 mm    |
| Width (inches) | 1.217 inch |                 |            |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -55...135 °C |
|-----------------------------|--------------|

## General data

|                                   |              |                                   |                                                           |
|-----------------------------------|--------------|-----------------------------------|-----------------------------------------------------------|
| Colour                            | white        | Halogen                           | Yes                                                       |
| Length                            | 10,000 mm    | Material                          | Polyolefine                                               |
| Operating temperature range       | -55...135 °C | Operating temperature range, max. | 135 °C                                                    |
| Operating temperature range, min. | -55 °C       | Recommended industries            | Plant manufacture, Energy, Device manufacturer, Machinery |
| Width                             | 30.9 mm      |                                   |                                                           |

## Conductor and cable markers

|                                   |                    |                                  |                         |
|-----------------------------------|--------------------|----------------------------------|-------------------------|
| Conductor O.D.                    | 6.4 - 19.1 mm      | Conductor O.D., max.             | 19.1 mm                 |
| Conductor O.D., min.              | 6.4 mm             | Conductor cross-section, max.    | 70 mm <sup>2</sup>      |
| Conductor cross-section, min.     | 16 mm <sup>2</sup> | Cross-section for connected wire | 16 - 70 mm <sup>2</sup> |
| Halogen                           | Yes                | Rate of shrinkage                | 3:1                     |
| Recommended shrinking temperature | 90 °C              | Text field height                | 30.7 mm                 |
| Text field width                  | 0 mm               |                                  |                         |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E366310 |

## Downloads

|                  |                              |
|------------------|------------------------------|
| Engineering Data | <a href="#">EPLAN, WSCAD</a> |
|------------------|------------------------------|

**HSS 6.4-19.1 EL W10M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

