

KSI/-16**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Insulated pin-cable connector made from PVC or PC/PA**

- Conventional designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 16 mm ² , 16 mm ²
Order No.	1491440000
Type	KSI/-16
GTIN (EAN)	4050118301427
Qty.	50 pc(s).

KSI/-16**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	4.86 g
------------	--------

Connectors

Conductor cross-section	16 mm ²	Conductor cross-section, max.	16 mm ²
Identification colour	blue	Inside diameter of collar (d4)	9.1 mm
Inside diameter of shaft (d1)	5.8 mm	Insulation	Available
Length 1 (l1)	40.7 mm	Length 2 (l2)	13.5 mm ²
Material/plastic	PA	Outside diameter of shaft (d3)	2.5 mm

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-92	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-92	ECLASS 11.0	27-40-02-92

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
------------------	-----------------------

KSI/-16

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

