

VSRI/0,1-0,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Insulated cable connector in PVC or PC/PA**

- Conventional designs
- Not soldered
- With conical entry funnel, except for joint connector

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 0.14 mm ² - 0.5 mm ²
Order No.	1491490000
Type	VSRI/0,1-0,5
GTIN (EAN)	4050118301533
Qty.	50 pc(s).

VSRI/0,1-0,5

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	0.52 g
------------	--------

Connectors

Conductor cross-section, max.	0.5 mm ²	Conductor cross-section, min.	0.14 mm ²
Identification colour	yellow	Inside diameter of collar (d4)	3.1 mm
Inside diameter of shaft (d1)	1.4 mm	Insulation	Fully insulated
Length 1 (l1)	24.5 mm	Length 2 (l2)	11.5 mm ²
Material/plastic	Polyolefine		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-12	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-12	ECLASS 11.0	27-40-02-12

Approvals

ROHS	Conform
------	---------

VSRI/0,1-0,5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

