

VSRI/4,0-6,0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Insulated cable connector in PVC or PC/PA

- Conventional designs
- Not soldered
- With conical entry funnel, except for joint connector

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 4 mm ² - 6 mm ²
Order No.	1491530000
Type	VSRI/4,0-6,0
GTIN (EAN)	4050118301724
Qty.	20 pc(s).

VSRI/4,0-6,0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	2.3 g
------------	-------

Connectors

Conductor cross-section, max.	6 mm ²	Conductor cross-section, min.	4 mm ²
Identification colour	yellow	Inside diameter of collar (d4)	6.5 mm
Inside diameter of shaft (d1)	3.6 mm	Insulation	Fully insulated
Length 1 (l1)	41 mm	Length 2 (l2)	15 mm ²
Material/plastic	Polyethylene		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-12	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-12	ECLASS 11.0	27-40-02-12

Approvals

ROHS	Conform
------	---------

VSRI/4,0-6,0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

