

VFSKHI/1,5-2,5/488**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Insulated tab-connector sleeves made from PVC
with copper sleeve**

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 1.5 mm ² - 2.5 mm ²
Order No.	1491710000
Type	VFSKHI/1,5-2,5/488
GTIN (EAN)	4050118301663
Qty.	100 pc(s).

VFSKHI/1,5-2,5/488**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Net weight	0.927 g	Weight	0.09 g
------------	---------	--------	--------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Connectors

Conductor cross-section, max.	2.5 mm ²	Conductor cross-section, min.	1.5 mm ²
Identification colour	blue	Insulation	Available
Length 1 (l1)	19.4 mm	Material/plastic	PVC
Plug-in density (d3)	0.8 mm	Plug-in width (d2)	4.8 mm

Classifications

ETIM 6.0	EC000516	ETIM 7.0	EC000516
ECLASS 9.0	27-44-03-92	ECLASS 9.1	27-40-02-90
ECLASS 10.0	27-44-03-92	ECLASS 11.0	27-44-03-92

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
------------------	-----------------------

VFSKHI/1,5-2,5/488

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

