

VFSKHI/4,0-6,0/9512**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Insulated tab-connector sleeves made from PVC
with copper sleeve**

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 4 mm ² - 6 mm ²
Order No.	1491760000
Type	VFSKHI/4,0-6,0/9512
GTIN (EAN)	4050118301588
Qty.	100 pc(s).

VFSKHI/4,0-6,0/9512**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Net weight	2.7 g	Weight	0.27 g
------------	-------	--------	--------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Connectors

Conductor cross-section, max.	6 mm ²	Conductor cross-section, min.	4 mm ²
Identification colour	yellow	Insulation	Available
Length 1 (l1)	28.6 mm	Material/plastic	PVC
Plug-in density (d3)	1.2 mm	Plug-in width (d2)	9.5 mm

Classifications

ETIM 6.0	EC000516	ETIM 7.0	EC000516
ECLASS 9.0	27-44-03-92	ECLASS 9.1	27-40-02-90
ECLASS 10.0	27-44-03-92	ECLASS 11.0	27-44-03-92

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
------------------	-----------------------

VFSKHI/4,0-6,0/9512

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

