

**KQN-M16/-240****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



**The use of insulated connectors guarantees users consistent electrical connection quality in the long term.**

- Wide range of insulated and non-insulated cable lugs and connectors
- Tubular cable lugs according to current market standards (Euroseries)
- Compression cable lugs acc. to DIN 46235
- Sheet metal cable lugs acc. to DIN 46234
- Insulated ring cable lugs to DIN 46237
- Insulated pin cable lugs to DIN 46231

**General ordering data**

|            |                                              |
|------------|----------------------------------------------|
| Version    | cable lug, terminal end, 240 mm <sup>2</sup> |
| Order No.  | <a href="#">1493480000</a>                   |
| Type       | KQN-M16/-240                                 |
| GTIN (EAN) | 4050118303209                                |
| Qty.       | 25 pc(s).                                    |

**KQN-M16/-240****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |        |         |
|------------|---------|--------|---------|
| Net weight | 145.3 g | Weight | 14.53 g |
|------------|---------|--------|---------|

**Connectors**

|                                |                     |                                |               |
|--------------------------------|---------------------|--------------------------------|---------------|
| Conductor cross-section        | 240 mm <sup>2</sup> | Connection length (l)          | 56 mm         |
| Hole                           | M 16                | Inside diameter of flange (d2) | 17 mm         |
| Inside diameter of shaft (d1)  | 23.5 mm             | Insulation                     | not available |
| Outside diameter of shaft (d3) | 38 mm               | Shaft length (a)               | 32 mm         |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001059    | ETIM 7.0    | EC001059    |
| ECLASS 9.0  | 27-40-02-12 | ECLASS 9.1  | 27-40-02-12 |
| ECLASS 10.0 | 27-40-02-12 | ECLASS 11.0 | 27-40-02-12 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                       |
|------------------|-----------------------|
| Engineering Data | <a href="#">EPLAN</a> |
|------------------|-----------------------|

## KQN-M16/-240

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

