

**KQNG-M3/-2,5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



**The use of insulated connectors guarantees users consistent electrical connection quality in the long term.**

- Wide range of insulated and non-insulated cable lugs and connectors
- Tubular cable lugs according to current market standards (Euroseries)
- Compression cable lugs acc. to DIN 46235
- Sheet metal cable lugs acc. to DIN 46234
- Insulated ring cable lugs to DIN 46237
- Insulated pin cable lugs to DIN 46231

**General ordering data**

|            |                                                                    |
|------------|--------------------------------------------------------------------|
| Version    | cable lug, terminal end, 1.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup> |
| Order No.  | <a href="#">1493600000</a>                                         |
| Type       | KQNG-M3/-2,5                                                       |
| GTIN (EAN) | 4050118303278                                                      |
| Qty.       | 100 pc(s).                                                         |

**KQNG-M3/-2,5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |        |        |
|------------|---------|--------|--------|
| Net weight | 0.641 g | Weight | 0.06 g |
|------------|---------|--------|--------|

**Connectors**

|                                |                     |                                |                     |
|--------------------------------|---------------------|--------------------------------|---------------------|
| Conductor cross-section, max.  | 2.5 mm <sup>2</sup> | Conductor cross-section, min.  | 1.5 mm <sup>2</sup> |
| Connection length (l)          | 11 mm               | Hole                           | C 3                 |
| Inside diameter of flange (d2) | 3.2 mm              | Inside diameter of shaft (d1)  | 2.3 mm              |
| Insulation                     | not available       | Outside diameter of shaft (d3) | 6 mm                |
| Shaft length (a)               | 5 mm                |                                |                     |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001059    | ETIM 7.0    | EC001059    |
| ECLASS 9.0  | 27-40-02-92 | ECLASS 9.1  | 27-40-02-12 |
| ECLASS 10.0 | 27-40-02-92 | ECLASS 11.0 | 27-40-02-92 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                       |
|------------------|-----------------------|
| Engineering Data | <a href="#">EPLAN</a> |
|------------------|-----------------------|

## KQNG-M3/-2,5

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

# Drawings

