

KQN-M5/-2,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The use of insulated connectors guarantees users consistent electrical connection quality in the long term.

- Wide range of insulated and non-insulated cable lugs and connectors
- Tubular cable lugs according to current market standards (Euroseries)
- Compression cable lugs acc. to DIN 46235
- Sheet metal cable lugs acc. to DIN 46234
- Insulated ring cable lugs to DIN 46237
- Insulated pin cable lugs to DIN 46231

General ordering data

Version	cable lug, terminal end, 1.5 mm ² - 2.5 mm ²
Order No.	1493890000
Type	KQN-M5/-2,5
GTIN (EAN)	4050118303605
Qty.	100 pc(s).

KQN-M5/-2,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight

0.977 g

Weight

0.1 g

Connectors

Conductor cross-section, max.

2.5 mm²

Connection length (l)

14 mm

Inside diameter of flange (d2)

5.3 mm

Insulation

not available

Shaft length (a)

5 mm

Conductor cross-section, min.

1.5 mm²

Hole

M 5

Inside diameter of shaft (d1)

2.3 mm

Outside diameter of shaft (d3)

10 mm

Classifications

ETIM 6.0

EC001059

ETIM 7.0

EC001059

ECLASS 9.0

27-40-02-12

ECLASS 9.1

27-40-02-12

ECLASS 10.0

27-40-02-12

ECLASS 11.0

27-40-02-12

Approvals

ROHS

Conform

Downloads

Engineering Data

[EPLAN](#)

KQN-M5/-2,5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

