

VSTN-M0,5/-0,75**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The use of insulated connectors guarantees users consistent electrical connection quality in the long term.

- Wide range of insulated and non-insulated cable lugs and connectors
- Tubular cable lugs according to current market standards (Euroseries)
- Compression cable lugs acc. to DIN 46235
- Sheet metal cable lugs acc. to DIN 46234
- Insulated ring cable lugs to DIN 46237
- Insulated pin cable lugs to DIN 46231

General ordering data

Version	cable lug, terminal end, 0.5 mm ² - 0.75 mm ²
Order No.	1497330000
Type	VSTN-M0,5/-0,75
GTIN (EAN)	4050118306637
Qty.	100 pc(s).

VSTN-M0,5/-0,75**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Dimensions and weights**

Net weight	0.75 g	Weight	0.08 g
------------	--------	--------	--------

Connectors

Conductor cross-section, max.	0.75 mm ²	Conductor cross-section, min.	0.5 mm ²
Connection length (l)	15 mm	Inside diameter of shaft (d1)	1.4 mm
Insulation	not available	Outside diameter of shaft (d3)	3 mm

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-12	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-12	ECLASS 11.0	27-40-02-12

Approvals

ROHS	Conform
------	---------

VSTN-M0,5/-0,75

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

