

FAD BLK1 SL24**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

The front adapters for migration are connected to the old PLC and, by means of a new pre-assembled cable, to the new one. Some adapters have 2 connectors for redundancy.

General ordering data

Order No.	1505520000
Type	FAD BLK1 SL24
GTIN (EAN)	4050118319538
Qty.	1 pc(s).

FAD BLK1 SL24**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Height	24 mm	Height (inches)	0.945 inch
Length	209.2 mm	Length (inches)	8.236 inch
Net weight	404.33 g	Width	37 mm
Width (inches)	1.457 inch		

Temperatures

Storage temperature	-40...60 °C	Operating temperature	-25...50 °C
---------------------	-------------	-----------------------	-------------

Connection data

Connection (field side)	SL 5.08 mm	Connection to PLC	TSX-BLK1
-------------------------	------------	-------------------	----------

Ratings data

Operating voltage	230 V AC / 320 V DC
-------------------	---------------------

Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	230 V AC
Surge voltage category	II	Pollution severity level	2
Pulse voltage test (1,2/50µs)	2.1 kV	Insulation test voltage	1.2 kVAC

Classifications

ETIM 6.0	EC002584	ETIM 7.0	EC002584
ECLASS 9.0	27-33-02-92	ECLASS 9.1	27-24-22-92
ECLASS 10.0	27-33-02-92	ECLASS 11.0	27-33-02-92

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
------------------	-----------------------

FAD BLK1 SL24

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

