

**IE-FM6Z2VO0200MLD0LD0X****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Industrial Ethernet connection technology by Weidmüller offers the optimal solution for the infrastructure of your machine, system or factory. All connection technology is available from one source.

The benefits for you:

- IEC-standardised connectors, in the variants 1, 4, 5 , 6 and 14
- consistently Cat. 6<sub>A</sub> with **STEADYTEC®** technology
- in IP20 and IP67
- all relevant industrial connections: RJ45, SC, ...
- comprehensive range of accessories

**General ordering data**

|            |                                                                                             |
|------------|---------------------------------------------------------------------------------------------|
| Version    | Pre-assembled patch cable, crossover, LC-Duplex IP 20, LC-Duplex IP 20, 62.5 µm, PVC, 200 m |
| Order No.  | <a href="#">1524920000</a>                                                                  |
| Type       | IE-FM6Z2VO0200MLD0LD0X                                                                      |
| GTIN (EAN) | 4050118329957                                                                               |
| Qty.       | 1 pc(s).                                                                                    |

**IE-FM6Z2V00200MLD0LD0X****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |                 |                |
|------------|---------|-----------------|----------------|
| Length     | 200 m   | Length (inches) | 7,874.016 inch |
| Net weight | 4,000 g |                 |                |

**Temperatures**

|                          |                |                       |               |
|--------------------------|----------------|-----------------------|---------------|
| Storage temperature      | -25 °C...75 °C | Operating temperature | -5 °C...75 °C |
| Installation temperature | -5 °C...50 °C  |                       |               |

**Fibre-optic**

|             |                                               |           |                                                 |
|-------------|-----------------------------------------------|-----------|-------------------------------------------------|
| Attenuation | ≤ 3.2 dB/km at 850 nm, ≤ 0.9 dB/km at 1300 nm | Bandwidth | ≥ 250 MHz*km at 850 nm, ≥ 600 MHz*km at 1300 nm |
| Fibre type  | GOF, Multimode, OM1                           |           |                                                 |

**Cable structure**

|                       |          |                  |         |
|-----------------------|----------|------------------|---------|
| Cable layout          | ZIPCORD  | Core diameter    | 62.5 µm |
| Material sheath       | PVC      | Primary coating  | 245 µm  |
| Sheath diameter       | 3*6 mm   | Sheathing colour | orange  |
| Standard designations | I-V(ZN)Y |                  |         |

**Mechanical and material properties of cable**

|                                |       |                                 |       |
|--------------------------------|-------|---------------------------------|-------|
| Min. bending radius, once only | 30 mm | Min. bending radius, repetitive | 60 mm |
|--------------------------------|-------|---------------------------------|-------|

**plug**

|                |                 |                 |                 |
|----------------|-----------------|-----------------|-----------------|
| Connector left | LC-Duplex IP 20 | Connector right | LC-Duplex IP 20 |
|----------------|-----------------|-----------------|-----------------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002607    | ETIM 7.0    | EC002607    |
| ECLASS 9.0  | 27-06-10-03 | ECLASS 9.1  | 27-06-10-03 |
| ECLASS 10.0 | 27-06-10-03 | ECLASS 11.0 | 27-06-10-03 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                                                                    |
|--------------------|--------------------------------------------------------------------|
| User Documentation | <a href="#">MAN IE GUIDE DE</a><br><a href="#">MAN IE GUIDE EN</a> |
|--------------------|--------------------------------------------------------------------|