

# Push-in X connector QSMX-4

Part number: 153379

FESTO



 General operating condition

## Data sheet

| Feature                                         | Value                                         |
|-------------------------------------------------|-----------------------------------------------|
| Size                                            | Mini                                          |
| Nominal width                                   | 2.5 mm                                        |
| Mounting position                               | Any                                           |
| Design                                          | X-shape                                       |
| Pack size                                       | 10                                            |
| Structural design                               | Push-pull principle                           |
| Operating pressure for entire temperature range | -0.095 MPa ... 0.6 MPa                        |
| Operating pressure for entire temperature range | -0.95 bar ... 6 bar                           |
| Operating pressure for entire temperature range | -13.775 psi ... 87 psi                        |
| Temperature-dependent operating pressure        | -0.095 MPa ... 1.4 MPa                        |
| Temperature-dependent operating pressure        | -0.95 bar ... 14 bar                          |
| Temperature-dependent operating pressure        | -13.775 psi ... 203 psi                       |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7:-:-] |
| Information on operating and pilot media        | Operation with oil lubrication possible       |
| Corrosion resistance class (CRC)                | 1 - Low corrosion stress                      |
| LABS (PWIS) conformity                          | VDMA24364-B1/B2-L                             |
| Ambient temperature                             | -10 °C ... 80 °C                              |
| Product weight                                  | 4 g                                           |
| No. of outlets                                  | 3                                             |
| No. of supply lines                             | 1                                             |
| Pneumatic connection 1                          | for pneumatic tubing outside diameter 4 mm    |
| Pneumatic connection 2                          | for pneumatic tubing outside diameter 4 mm    |
| Releasing ring color                            | Blue                                          |
| Note on materials                               | RoHS-compliant                                |
| Housing material                                | PBT                                           |
| Releasing ring material                         | POM                                           |
| Material of tubing seal                         | NBR                                           |
| Material of tube retaining claw                 | High-alloy stainless steel                    |