

IE-FCI-PWB-RCBO**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

General ordering data

Version	FrontCom, Residual current operated circuit breaker with overcurrent protection (RCBO), Insert Power large, RCBO
Order No.	1534250000
Type	IE-FCI-PWB-RCBO
GTIN (EAN)	4050118337938
Qty.	1 pc(s).

IE-FCI-PWB-RCBO

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	71.718 g
------------	----------

Temperatures

Operating temperature	-5 °C...40 °C
-----------------------	---------------

General data

Insert type	Product type	Residual current operated circuit breaker with overcurrent protection (RCBO)
Protection degree	Insert Power large IP20	

Clampable conductors

Conductor connection cross-section, extremely flexible with wire end ferrule	1.5 ... 2.5 mm ²
--	-----------------------------

Conductor connection cross-section, extremely flexible with wire end ferrule	min.	1.5 mm ²
	max.	2.5 mm ²

Conductor connection cross-section, flexible with wire end ferrule	min.	1.5 mm ²
	max.	2.5 mm ²

Conductor connection cross-section, flexible with wire end ferrule	1.5 ... 2.5 mm ²
--	-----------------------------

Conductor connection cross-section, rigid	1.5 ... 2.5 mm ²
---	-----------------------------

Conductor connection cross-section, rigid	min.	1.5 mm ²
	max.	2.5 mm ²

Type of connection	Screw connection
--------------------	------------------

General standards

Certificate No. (GERMLLOYD)	13866-15
-----------------------------	----------

Technical data

I _{Δm}	500 A	I _{Δn}	30 mA
Operating voltage	230 V AC	Rated current	16 A
Triggering characteristic	Typ C	Type of connection	Screw connection

Classifications

ETIM 6.0	EC001121	ETIM 7.0	EC001121
ECLASS 9.0	27-44-03-90	ECLASS 9.1	27-18-90-90
ECLASS 10.0	27-44-03-90	ECLASS 11.0	27-44-03-90

Approvals

Approvals



IE-FCI-PWB-RCBO

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Downloads

Approval/Certificate/Document of
Conformity

[GL_FrontCom](#)

Engineering Data

[STEP](#)

User Documentation

[MAN IE GUIDE DE](#)

[MAN IE GUIDE EN](#)

[Designation key / Type key](#)

[Manual](#)

IE-FCI-PWB-RCBO

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Triggering characteristic

