

IE-FC-SET-IPDEK001-KY-P**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

General ordering data

Version	FrontCom, Set
Order No.	1543680000
Type	IE-FC-SET-IPDEK001-KY-P
GTIN (EAN)	4050118348842
Qty.	1 pc(s).
Reference product	1450520000 1450630000 1450730000 1019570000 1962840000 1450820000

Creation date March 24, 2021 5:39:15 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-FC-SET-IPDEK001-KY-P

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	134 mm	Depth (inches)	5.276 inch
Height	40 mm	Height (inches)	1.575 inch
Net weight	493.15 g	Width	67 mm
Width (inches)	2.638 inch		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1, Potassium perfluorobutane sulfonate 29420-49-3
------------	--

General data

Material cover	Polycarbonate PC	
Material frame	Zinc diecast	
Product type	Set	
Protection degree	IP65, in closed state	
Reference product	Cardinality	1
	Reference	IE-FC-SFP-KEY2
	Cardinality	1
	Reference	IE-FC-IP-PWB/2ST
	Cardinality	1
	Reference	IE-FCI-PWB-DE
	Cardinality	1
	Reference	IE-BI-USB-A
	Cardinality	1
	Reference	IE-BI-RJ45-C
	Cardinality	1
	Reference	IE-FC-PWPC

Technical data

Data inserts	USB 2.0 A/A, RJ45 coupling Cat.6 _A	Frame	Plastic cover, Lockable with key
Insert plate	2x data, 1x power, Unshielded	Power inserts	Socket DE
Printing	Incl. fixed inscription: "Service only!", "USB", "Ethernet", "230 V AC"	Protection degree	IP65, in closed state
Rated current for socket	16 A	Rated voltage for socket	250 V

General standards

Certificate No. (GERMLLOYD)	13866-15
-----------------------------	----------

Classifications

ETIM 6.0	EC001031	ETIM 7.0	EC001031
ECLASS 9.0	27-18-27-02	ECLASS 9.1	27-18-27-90
ECLASS 10.0	27-18-27-02	ECLASS 11.0	27-18-27-02

IE-FC-SET-IPDEK001-KY-P

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of
Conformity

[GL_FrontCom](#)

Engineering Data

[STEP](#)

User Documentation

[MAN IE GUIDE DE](#)

[MAN IE GUIDE EN](#)

IE-FC-SET-IPDEK001-KY-P

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

