# AEP 2T 2.5 BL

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

## Product image

**Spring connection with PUSH IN Technology**
The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

### General ordering data

| | |
|---|---|
| Version | A-series, End plate |
| Order No. | 1547700000 |
| Type | AEP 2T 2.5 BL |
| GTIN (EAN) | 4050118441055 |
| Qty. | 20 pc(s). |

# AEP 2T 2.5 BL

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

| | | | |
|---|---|---|---|
| Depth | 43.1 mm | Depth (inches) | 1.697 inch |
| Height | 88.25 mm | Height (inches) | 3.474 inch |
| Net weight | 3.4 g | Width | 2.1 mm |
| Width (inches) | 0.083 inch | | |

### Temperatures

| | | | |
|---|---|---|---|
| Storage temperature | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C | | |

### Material data

| | | | |
|---|---|---|---|
| Material | Wemid | Colour | blue |
| UL 94 flammability rating | V-0 | | |

### System specifications

| | |
|---|---|
| Version | End plate |

### Additional technical data

| | | | |
|---|---|---|---|
| Snap-on | Yes | With snap-in pegs | Yes |

### Classifications

| | | | |
|---|---|---|---|
| ETIM 6.0 | EC000886 | ETIM 7.0 | EC000886 |
| ECLASS 9.1 | 27-14-11-33 | ECLASS 10.0 | 27-14-11-33 |
| ECLASS 11.0 | 27-14-11-33 | | |

### Approvals

| | |
|---|---|
| ROHS | Conform |

### Downloads

| | |
|---|---|
| Engineering Data | STEP |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| User Documentation | StorageConditionsTerminalBlocks |